

**PRODUCT-DETAILS** 

## Sentry SSR10P Sentry SSR10P Safety relay



| General Information   |  |
|-----------------------|--|
| Extended Product Type | Sentry SSR10P  |
| Product ID            | 2TLA010050R0001  |
| EAN                   | 7350024486254  |
| Catalog Description   | Sentry SSR10P Safety relay   |
|                       | Sentry SSR10P Safety relay with relay outputs 3NO+1NC, +24 VDC supply voltage and<br>push-in spring terminals.<br>For monitoring of safety devices with contacts, 1 or 2 equivalent channels , and safety<br>devices with OSSD outputs.<br>Manual or automatic reset selectable by switch on front.  |
| Long Description      | Sentry safety relays cover various types of safety applications up to PLe / SIL3.<br>Basic models provide reliable supervision of simpler safety functions, while universal models<br>provide advanced features and high flexibility.<br>Models with display offer preset configurations and extensive information to further simplify<br>troubleshooting.   |
|                       | Additional variants offer a high accuracy timer function of ± 1% and an adjustable time<br>setting range from 0-999 s.<br>High output current capacity of up to 6 A can save the use of an intermediary contactor.<br>Multi-reset allows up to 10 safety relays connected to one reset light-button.<br>All models are available with detachable push-in or screw terminals. Terminals and coding<br>kit to mark removed terminals are available as accessories. |

| Ordering               |               |
|------------------------|---------------|
| EAN                    | 7350024486254 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85364900      |

| Popular Downloads                    |                                    |
|--------------------------------------|------------------------------------|
| Data Sheet, Technical<br>Information | 2TLC010037L0201                    |
| Instructions and Manuals             | 2TLC010063M0201                    |
| CAD Dimensional<br>Drawing           | 2CDC001079B0201                    |
| Dimension Diagram                    | 2TLC010001U0201                    |
| Wiring Diagram                       | 2TLC010007T0001                    |
| Marketing Video                      | 2TLC010019N0201<br>2TLC010018N0201 |

| Dimensions                    |          |
|-------------------------------|----------|
| Product Net Width             | 22.5 mm  |
| Product Net Height            | 120 mm   |
| Product Net Depth /<br>Length | 120 mm   |
| Product Net Weight            | 0.207 kg |

| Technical   |   |
|---|---|
| Function  | Safety relay for monitoring of safety devices   |
| Sub-Function                                      | Start/test input, Manual/Auto reset selectable by switch  |
| Timer Relay Type                                  | No Time Delay   |
| Rated Control Supply<br>Voltage (U <sub>s</sub> ) | 24 V DC   |
| Degree of Protection                              | IP20  |
| Connecting Capacity                               | Crimped Pin 1x0.22.5 mm <sup>2</sup><br>Crimped Pin 2x0.251.5 mm <sup>2</sup><br>Flexible with Ferrule 1x0.22.5 mm <sup>2</sup><br>Flexible with Ferrule 2x0.251.5 mm <sup>2</sup><br>Solid 1x0.22.5 mm <sup>2</sup><br>Solid 2x0.251.5 mm <sup>2</sup> |
| Wire Stripping Length                             | 6.5 mm  |
| Mounting on DIN Rail                              | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715  |
| Standards   | ISO 1384 <u>9</u>   |

| Technical UL/CSA              |  |
|-------------------------------|--|
| Connecting Capacity<br>UL/CSA | Crimped Pin 1x 24-14 AWG<br>Flexible with Ferrule 1x 24-14 AWG<br>Solid 1x 24-14 AWG |
|                               |  |

| Environmental           |  |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 +65 °C<br>Storage -40 +70 °C |
| RoHS Status             | Following EU Directive 2011/65/EU          |

| Certificates and Declarations       |                     |
|-------------------------------------|---------------------|
| CQC Certificate                     | CQC2017010303977544 |
| cUL Certificate                     | 2TLC010006D0201     |
| Declaration of Conformity<br>- CCC  | 2020980303000244    |
| Declaration of Conformity<br>- CE   | 2TLC010010D0201     |
| Declaration of Conformity<br>- UKCA | 2TLC010190D0201     |
| TÜV Certificate                     | 2TLC010008D0201     |

Subject to change without notice

| Container Information             |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 125 mm        |
| Package Level 1 Depth /<br>Length | 31 mm         |
| Package Level 1 Height            | 129 mm        |
| Package Level 1 Gross<br>Weight   | 0.268 kg      |
| Package Level 1 EAN               | 7350024486254 |
| Package Level 2 Units             | 36 piece      |
| Package Level 2 Width             | 280 mm        |
| Package Level 2 Depth /<br>Length | 395 mm        |
| Package Level 2 Height            | 210 mm        |
| Package Level 2 Gross<br>Weight   | 9.9 kg        |

| Object Classification Code | ŀ   |
|----------------------------|---|
| ETIM 7                     | EC001449 - Device for monitoring of safety-related circuit  |
| ETIM 8                     | EC001449 - Device for monitoring of safety-related circuits |
| ETIM 9                     | EC001449 - Device for monitoring of safety-related circuits |
| eClass                     | V11.0 : 2737181   |
| UNSPSC                     | 3912233   |
| E-Number (Finland)         | 2712897   |
| E-Number (Sweden)          | 3861403   |

| Accessories     |                            |             |          |                    |
|-----------------|----------------------------|-------------|----------|--------------------|
| Identifier      | Description                | Туре        | Quantity | Unit Of<br>Measure |
| 2TLA010099R0000 | Sentry S30A Terminal block | Sentry S30A | 1        | piece              |
| 2TLA010099R0100 | Sentry S30B Coding kit     | Sentry S30B | 1        | piece              |
| 2TLA010099R0001 | Sentry S30C Terminal block | Sentry S30C | 1        | piece              |

## Categories

Low Voltage Products and Systems  $\rightarrow$  Control Products  $\rightarrow$  Electronic Relays and Controls  $\rightarrow$  Safety Relays  $\rightarrow$  Single Function Safety Relays

 $\label{eq:low-Voltage-Products-Safety-Produc$ 





© 2023 ABB. All rights reserved.