

PRODUCT-DETAILS

Sentry SSR20MP Sentry SSR20MP Safety relay



General Information	
Extended Product Type	Sentry SSR20MP
Product ID	2TLA010051R0101
EAN	7350024486285
Catalog Description	Sentry SSR20MP Safety relay
	Sentry SSR20MP Safety relay with relay outputs 3NO+1NC, 85-265 VAC/120-375 VDC supply voltage and push-in spring terminals. For monitoring of two-hand devices. Manual or automatic reset selectable by switch on front.
Long Description	Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility. Models with display offer preset configurations and extensive information to further
	simplify troubleshooting. Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s. High output current capacity of up to 6 A can save the use of an intermediary
	contactor. Multi-reset allows up to 10 safety relays connected to one reset light- button. All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories.

Ordering	
EAN	7350024486285
Minimum Order Quantity	1 piece

© 2023 ABB. All rights reserved.

Popular Downloads	
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010066M0201
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010010T0001
Marketing Video	2TLC010019N0201 2TLC010018N0201

Dimensions		
Product Net Width	22.5 mm	
Product Net Height	120 mm	
Product Net Depth / Length	120 mm	
Product Net Weight	0.214 kg	

Technical		
Function	Safety relay for monitoring of two-hand devices	
Sub-Function	Start/test input, Manual/Auto reset selectable by switch	
Timer Relay Type	No Time Delay	
Rated Control Supply Voltage (U _s)	120 375 V DC 85 265 V AC	
Degree of Protection	IP20	
Connecting Capacity	Crimped Pin 1x0.22.5 mm Crimped Pin 2x0.251.5 mm Flexible with Ferrule 1x0.22.5 mm Flexible with Ferrule 2x0.251.5 mm Solid 1x0.22.5 mm Solid 2x0.251.5 mm	
Wire Stripping Length	6.5 mm	
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715	
Standards	ISO 13849	

Technical UL/CSA	
Connecting Capacity	Crimped Pin 1x 24-14 AW
UL/CSA	Flexible with Ferrule 1x 24-14 AW
	Solid 1x 24-14 AW
Environmental	
Ambient Air	Operation -25 +65 °

Following EU Directive 2011/65/EU

Certificates and Declarations

© 2023 ABB. All rights reserved.

RoHS Status

CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
TÜV Certificate	2TLC010008D0201

Container Information

Package Level 1 Units	box 1 piece	
Package Level 1 Width	125 mm	
Package Level 1 Depth / Length	31 mm	
Package Level 1 Height	129 mm	
Package Level 1 Gross Weight	0.275 k	
Package Level 1 EAN	7350024486285	
Package Level 2 Units	36 piece	
Package Level 2 Width	280 mm	
Package Level 2 Depth / Length	395 mm	
Package Level 2 Height	210 mm	
Package Level 2 Gross Weight	10.2 kg	

Classifications	
Object Classification Code	к
ETIM 7	EC001452 - Two-hand control relay
ETIM 8	EC001452 - Two-hand control relay
ETIM 9	EC001452 - Two-hand control relay
eClass	V11.0 : 27371821
UNSPSC	39122331
E-Number (Finland)	2712900
E-Number (Sweden)	3861409

Accessories				
Identifier	Description	Type Quantity		Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

Categories

© 2023 ABB. All rights reserved.

Low Voltage Products and Systems \rightarrow Control Products \rightarrow Electronic Relays and Controls \rightarrow Safety Relays \rightarrow Single Function Safety Relays

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems}\ \to\ \mathsf{Control}\ \mathsf{Products}\ \to\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Single}\ \mathsf{Function}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Safety}\ \mathsf{Relays}\ \to\ \mathsf{Safety}\ \mathsf{Saf$

