

PRODUCT-DETAILS

## Sentry TSR20 Sentry TSR20 Safety relay



General Information	
Extended Product Type	Sentry TSR20
Product ID	2TLA010061R0000
EAN	7350024483352
Catalog Description	Sentry TSR20 Safety relay
	Sentry TSR20 Safety relay with delayed relay outputs 3NO+1NC +24VDC nower supply

entry TSR20 Safety relay with delayed relay outputs 3NO+1NC, +24VDC power supply and screw terminals.

For monitoring of safety devices with contacts, 1 or 2 equivalent channels, and safety devices with OSSD outputs.

OFF-delay time (0,5s or 1,5s) selectable by switch on the front.

Long Description

Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility. Models with display offer preset configurations and extensive information to further simplify troubleshooting.

Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s. High output current capacity of up to 6 A can save the use of an intermediary contactor. Multi-reset allows up to 10 safety relays connected to one reset light-button. All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories.

 Ordering
 7350024483352

 Minimum Order Quantity
 1 piece

 Customs Tariff Number
 85364900

Sentry TSR20 2

Popular Downloads	
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals CAD Dimensional Drawing	2TLC010070M0201 2CDC001079B0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010014T0001
Marketing Video	2TLC010019N0201
	2TLC010018N0201
Dimensions	
Product Net Width	22.5 mm
Product Net Height	120 mm
Product Net Depth / Length	120 mm
Product Net Weight	0.207 kg
Technical	
Function	Safety relay for monitoring of safety devices
Sub-Function	Start/test input, Auto reset only, Time delay selectable by switch
Timer Relay Type	OFF-Delay
Time Range	0.5 and 1.5 seconds
Rated Control Supply Voltage (U <sub>s</sub> )	24 V DC
Degree of Protection	IP20
Connecting Capacity	Crimped Pin 1x0.23.3 mm² Crimped Pin 2x0.21.5 mm² Flexible with Ferrule 1x0.23.3 mm² Flexible with Ferrule 2x0.21.5 mm² Solid 1x0.23.3 mm²
Tightening Torque	Solid 2x0.21.5 mm² 0.7 N·m
Wire Stripping Length	6.5 mm
Recommended Screw Driver	M3.5
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	ISO 13849
Technical UL/CSA	
Connecting Capacity	Crimped Pin 1x 24-12 AWG
UL/CSA	Crimped Pin 2x 24-16 AWG
	Flexible with Ferrule 1x 24-12 AWG Flexible with Ferrule 2x 24-16 AWG
	Solid 1x 24-12 AWG Solid 2x 24-16 AWG
Environmental	
Ambient Air Temperature	Operation -25 +65 °C
Dol IC Ctatus	Storage -40 +70 °C
RoHS Status	Following EU Directive 2011/65/EU
Certificates and Declarations	
CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201
COL DETUICATE	21LC010000D0201

Sentry TSR20 3

cULus Certificate	2TLC010007D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
KC Certificate	2TLC010048D0201
TÜV Certificate	2TLC010008D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	31 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.268 kg
Package Level 1 EAN	7350024483352
Package Level 2 Units	36 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	9.9 kg

Classifications	
Object Classification Code	<u>K</u>
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
UNSPSC	39122331
E-Number (Finland)	2712529
E-Number (Sweden)	3860826

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

## Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{Control Products} \rightarrow \mbox{Electronic Relays and Controls} \rightarrow \mbox{Safety Relays} \rightarrow \mbox{Expansion Relays} \\ \mbox{Low Voltage Products and Systems} \rightarrow \mbox{Control Products} \rightarrow \mbox{Safety Products} \rightarrow \mbox{Safety Relays} \rightarrow \mbox{Expansion Relays} \\ \mbox{Expansion Relays} \rightarrow \m$ 

Sentry TSR20 4





