

PRODUCT-DETAILS

Sentry USR22P Sentry USR22P Safety relay



General Information	
Extended Product Type	Sentry USR22P
Product ID	2TLA010070R0401
EAN	7350024486353
Catalog Description	Sentry USR22P Safety relay

Sentry USR22P Universal safety relay with relay outputs 2NO+2 delayable NO, +24VDC power supply and push-in spring terminals.

For monitoring of safety devices with contacts, 1 or 2 equivalent or antivalent channels, safety devices with OSSD outputs, two-hand devices, safety mats and safety

edges/bumpers. Timer function 0-999 seconds with a better accuracy than 1%: OFF-delay, ON-delay, Time

bypass and Time reset.

A display on front facilitates configuration and troubleshooting by displaying error codes and

error log. A custom configuration can be protected by password.

Manual or automatic reset selectable.

Long Description

Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility.

Models with display offer preset configurations and extensive information to further simplify troubleshooting.

Additional variants offer a high accuracy timer function of ± 1% and an adjustable time

setting range from 0-999 s. High output current capacity of up to 6 A can save the use of an intermediary contactor.

High output current capacity of up to 6 A can save the use of an intermediary contactor.

Multi-reset allows up to 10 safety relays connected to one reset light-button.

All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories

Ordering

EAN 7350024486353

Sentry USR22P 2

Customs Tariff Number	85364900
Danulas Davida da	
Popular Downloads Data Sheet, Technical	2TLC010037L0201
Information Instructions and Manuals	2TI C010072M0201
CAD Dimensional	2TLC010073M0201 2CDC001079B0201
Drawing	
Dimension Diagram	2TLC010001U0201
Wiring Diagram Marketing Video	2TLC010017T0001 2TLC010019N0201
ivial neuring video	2TLC010018N0201
Dimensions	
Product Net Width	22.5 mm
Product Net Height	120 mm
Product Net Depth / Length	120 mm
Product Net Weight	0.229 kg
Technical	
Function	Safety relay for monitoring of safety devices
Sub-Function	Start/test input, configurable Manual/Auto reset and Timer, Display (error indication and error log)
Timer Relay Type	Multifunction
Time Range	0 999 seconds
Rated Control Supply Voltage (U _s)	24 V DC
Degree of Protection	IP20
Connecting Capacity	Crimped Pin 1x0.22.5 mm² Crimped Pin 2x0.251.5 mm² Flexible with Ferrule 1x0.22.5 mm² Flexible with Ferrule 2x0.22.5 mm² Solid 1x0.22.5 mm² Solid 2x0.251.5 mm²
Wire Stripping Length	6.5 mm
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	ISO 13849
Technical UL/CSA	
Connecting Capacity UL/CSA	Crimped Pin 1x 24-14 AWG Flexible with Ferrule 1x 24-14 AWG Solid 1x 24-14 AWG
Environmental	
Ambient Air Temperature	Operation -25 +65 °C
	Storage -40 +70 °C
RoHS Status	Following EU Directive 2011/65/EU
Certificates and Declarations	
CQC Certificate Declaration of Conformity	CQC2017010303977544 20209803030000244
© 2022 ARR All vieles recorded	2022/00/11 Cubicet to about

Minimum Order Quantity

1 piece

Sentry USR22P 3

- CCC	
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
TÜV Certificate	2TLC010008D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	31 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.29 kg
Package Level 1 EAN	7350024486353
Package Level 2 Units	36 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	10.7 kg

Classifications	
Object Classification Code	K
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
UNSPSC	39122331
E-Number (Finland)	2712907
E-Number (Sweden)	3861423

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Control\ Products\ \rightarrow\ Electronic\ Relays\ and\ Controls\ \rightarrow\ Safety\ Relays\ \rightarrow\ Safety\ Timers$

 $Low\ Voltage\ Products\ \rightarrow\ Control\ Products\ \rightarrow\ Electronic\ Relays\ and\ Controls\ \rightarrow\ Safety\ Relays\ \rightarrow\ Universal\ Safety\ Nelays\ \rightarrow\ Universal\ Safety\$

 $Low\ Voltage\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Relays\ \rightarrow\ Safety\ Timers$

 $Low\ Voltage\ Products \rightarrow Safety\ Products \rightarrow Safety\ Products \rightarrow Safety\ Relays \rightarrow Universal\ Safety\ Relays \rightarrow Univ$

Sentry USR22P 4



