

PRODUCT-DETAILS

9T33C2680 9T33C2680 Low Voltage Dry Type Transformer-LPT



| General Information | |
|-------------------------|--|
| Global Commercial Alias | 9T33C2680 |
| Extended Product Type | 9T33C2680 |
| Product ID | 1TQX333711A0609 |
| EAN | 783173366257 |
| Catalog Description | 9T33C2680 Low Voltage Dry Type Transformer-LPT |
| Long Description | ABB's 9T33 line of Low Voltage Dry Type Single-phase transformers are for applications requiring a 3-wire secondary voltage for 120/240 V systems. These QL transformers come in standard NEMA 2 enclosures with rain shield kits available as accessories for NEMA 3R installations. The transformer is used to obtain the load voltage from the distribution voltage while providing galvanic isolation. |

| Technical | |
|--|--|
| Current Type | AC |
| Primary Voltage | 300 V AC ;600 V AC |
| Secondary Voltage | 120 V AC 240 V AC |
| Primary Rated Impulse Withstand Voltage | 10 kV |
| Frequency (f) | 60 Hz |
| Apparent Power Output | 15 kV·A |
| Connection Configuration | 1Ph, SeriesXParallel, 3 wire secondary |
| Number of Phases | 1 |
| Insulation Class | 220°C,ClassR |
| Surge Suppression | Not Included |

9T33C2680 2

| Accessory Type | Rain Shield kits, Lug Kits, Wall Mount Kits |
|-----------------------------------|---|
| Enclosure Type NEMA | Type2 |
| Transformer Type | General Purpose |
| Ventilation Type | Passive |
| Housing Material | Painted Steel |
| Material of Conductor | Copper |
| Accessories Available | Yes |
| Color | ANSI 61 Gray |
| Number of Batteries | 0 |
| Frame Size | YX171 |
| | |
| Environmental | |
| Ambient Temperature | 40 °C |
| Degree of Protection | Housing IP22 |
| RoHS Status | No declaration needed |
| REACH Declaration | No declaration needed |
| Conflict Minerals | 9AKK108468A3363 |
| Reporting Template (CMRT) | 9ANN 100400A3303 |
| | |
| Dimensions | |
| Product Net Width | 26.2 in 665.5 mm |
| Product Net Height | 34.7 in 881.4 mm |
| Product Net Depth / Length | 18.4 in 467.4 mm |
| Product Net Weight | 350 lb 158.8 kg |
| Dimension Diagram | 303B409CAP071 |
| | |
| Ordering | |
| Minimum Order Quantity | 1 piece |
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross | 397 lb |
| Weight | 180.1 kg |
| Certificates and Declarations | |
| | No dealersting and dealers |
| Declaration of Conformity - CE | No declaration needed |
| | |
| Installation | |
| Instructions and Manuals | 9AKK107991A2142 |
| Popular Downloads | |
| Data Sheet, Technical Information | 1TQC1935E0001 |
| | |
| | |

Classifications

9T33C2680 3

| ETIM 9 | EC004582 - Low voltage dry type transformer |
|----------------------------|---|
| WEEE Category | Product Not in WEEE Scope |
| WEEE B2C / B2B | Business To Business |
| UNSPSC | 39121001 |
| Object Classification Code | ТД |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow LV\ Dry\ Type\ Transformers \rightarrow Large\ Power\ Transformers$





