

PRODUCT-DETAILS

E215-16-11F

E215-16-11F Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 1NC, 0CO, EI. Color: Black, MW: 0.5



General Information

Extended Product Type	E215-16-11F
Product ID	2CCA703154R0001
EAN	7612270938858
Catalog Description	E215-16-11F Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 1NC, 0CO, EI. Color: Black, MW: 0.5
Long Description	Pushbutton 1 NO + 1 NC, Rated current: 16A/250 VACPDC, Button colour: black, Module width 0,5

Technical

Standards	EN60068-2-1 EN60068-2-2 EN60068-2-30 DIN EN 60669-1 VDE 0632-1 UL508
Rated Voltage (U_r)	Lamp 48 ... 48 V
Rated Operational Voltage	acc. to EN 250 V AC acc. to UL 508 240 V AC
Maximum Switching Voltage	250 V
Rated Current (I_n)	16 A
Rated Frequency (f)	50/60 Hz
Power Loss	0.5 W
Power Watt	0.72 W

Number of Poles	2
Number of Contacts CO	0
Number of Contacts NC	1
Number of Contacts NO	1
Number of Main Contacts NC	1
Number of Main Contacts NO	1
Number of Auxiliary Contacts CO (SPDT)	0
Tightening Torque	1.2-1.5 N·m
Switch Type	Double Interrupting Contacts
Material of Conductor	Copper
Options Provided	1 NO + 1 NC
Remarks	Sealable in the On and Off positions
Color	Black
Control Element Color	Black
Connecting Capacity	Solid 1x1..6 mm ² Solid 2x2.5 mm ² Flexible 1x0.75..2x2.5 mm ²

Environmental

Ambient Air Temperature	Operation -25...+55 °C Storage -40...+70 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	2CCC441014D0201
REACH Declaration	2CCC005047D0201
Environmental Information	2CCC441003C0201
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	0.5
Product Net Width	9 mm
Product Net Height	85 mm
Product Net Depth / Length	68 mm
Product Net Weight	49 g
Built-In Depth (t ₂)	75 mm

Ordering

Minimum Order Quantity	10 piece
Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	496 g
E-Number (Finland)	2312349
E-Number (Switzerland)	467560258

Certificates and Declarations

CB Certificate	9AKK108466A3845
CCC Certificate	9AKK108466A3830
Declaration of Conformity - CE	2CCC441014D0201
Declaration of Conformity - UKCA	9AKK108467A6137
EAC Certificate	9AKK107991A4779
VDE Certificate	9AKK107991A9822

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CCC441003C0101
--------------------------------------	-----------------

Classifications

ETIM 8	EC001546 - Push button for distribution board
ETIM 9	EC001546 - Push button for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365053
UNSPSC	39122216
eClass	V11.0 : 27142302
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
Object Classification Code	S

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

