

PRODUCT-DETAILS

# OS60GJ22F

## OS60GJ22F FUSIBLE DISCONNECT SWITCH



### General Information

Extended Product Type	OS60GJ22F
Product ID	1SCA115468R1001
EAN	6417019478173
Catalog Description	OS60GJ22F FUSIBLE DISCONNECT SWITCH
Long Description	Switch Fuses,Front Operated,4-pole,22 (Between the Poles),Class J,60 A,Handle and shaft not included,Switched - Fusible Pole

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

---

## Popular Downloads

---

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311036M0212

---

## Dimensions

---

Product Net Width	180 mm
Product Net Height	112 mm
Product Net Depth / Length	118 mm
Product Net Weight	1.4 kg

---

## Technical

---

Rated Operational Current AC-21A ( $I_e$ )	(500 V) 60 A (690 V) 60 A
Rated Operational Current AC-22A ( $I_e$ )	(500 V) 60 A (690 V) 60 A
Rated Operational Current AC-23A ( $I_e$ )	(500 V) 60 A (690 V) 60 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 18.5 kW (400 V) 30 kW (415 V) 30 kW (500 V) 37 kW (690 V) 55 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40$ °C 63 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kiloampere rms
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 7.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Type	Switched - Fusible Pole
Switches Operating Mechanism	22 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	60 A

Fuse System	Class J
Operating Mode	Front Operated
Standards	UL98 IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	2.5 ... 25 mm <sup>2</sup>
Terminal Type	Screw Terminals
Rated Current (I <sub>n</sub> )	Main Circuit 60 A

## Technical UL/CSA

Ampere Rating	60 A
Horsepower Rating UL/CSA	(acc. to UL 240 V) 15 Hp (acc. to UL 480 V) 30 Hp (acc. to UL 600 V) 50 Hp
Tightening Torque UL/CSA	Wire-Clamp 30 in-lb Wire-Clamp 35 in-lb

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

## Certificates and Declarations (Document Number)

CCC Certificate	CCC OS32-63G_ 2016.pdf
Declaration of Conformity - CE	1SCC311136D2703
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_ .pdf
Instructions and Manuals	1SCC311036M0212
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm 5.7 in
Package Level 1 Gross Weight	1.9 kg 4.2 lb
Package Level 1 EAN	6417019478173

---

## Classifications

---

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
ETIM 8	EC001040 - Fuse switch disconnecter
ETIM 9	EC001040 - Fuse switch disconnecter
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnecter
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---



---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Fuses

