

PRODUCT-DETAILS

# ZLS905E46-3LN

## ZLS905E46-3LN Starter pack



### General Information

Extended Product Type	ZLS905E46-3LN
Product ID	2CCA183127R0001
EAN	7612271413606
Catalog Description	ZLS905E46-3LN Starter pack
Long Description	Starter pack Touch proof with 46 Modules L1,L2,L3 N Pluggable socket system SMISSLINE TP is completely fingersafe (IP2XB) together with the socket end piece

### Technical

Standards	IEC/EN 61439-6
Rated Operational Voltage	690/1000 V AC/DC
Rated Current (I <sub>n</sub> )	125 A
Surface Finishing	Tinned
Options Provided	3LN
Model Number	Flat

### Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK107991A9646
Environmental Information	9AKK108467A9561
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

---

## Dimensions

Product Net Width	111 mm
Product Net Height	869 mm
Product Net Depth / Length	34 mm
Product Net Weight	1645 g
Dimension Diagram	9AKK107492A6192

---

## Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	1823 g
E-Number (Switzerland)	809993730

---

## Certificates and Declarations

Declaration of Conformity - CE	9AKK107991A9646
--------------------------------	-----------------

---

## Installation

Instructions and Manuals	9AKK107680A2315
--------------------------	-----------------

---

## Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
-----------------------------------	-----------------

---

## Classifications

ETIM 8	EC001522 - Busbar
ETIM 9	EC001522 - Busbar
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389030
UNSPSC	39121117
eClass	V11.0 : 27370303
IDEA Granular Category Code (IGCC)	4376 >> Distributor assembly busbars
Object Classification Code	W

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A

