

Product Detail | FC-302P75KT5E66H2XGXXXXSXXXXAXBXXXXDX



131H7152

FC-302P75KT5E66H2XGXXXXSXXXXAXBXXXXDX

Frequency converter
FC-302P75KT5E66H2XGXXXXSXXXXAXBXXXXDX
VLT® AutomationDrive FC-302
(P75K) 75 KW / 100 HP,
Three phase, 380 - 500 VAC, (E66) IP66 / NEMA 4X
RFI Filter
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: C2
No A Option, No B Option
No C1 option, No D option

Other options according to Model code

Model code: FC-302P75KT5E66H2XGXXXXSXXXXAXBXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

View Efficiency Data

PRODUCT DETAILS

Gross weight		58.93 Kilogram
Net weight		55.59 Kilogram
Volume		228.095 Liter
EAN		5702427576087
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® AutomationDrive FC-
Series	302	302
Power Rating	P75K	(P75K) 75 KW / 100 HP
Phase	T	Three phase
Mains Voltage	5	380 - 500 VAC
Enclosure	E66	(E66) IP66 / NEMA 4X
RFI Filter	H2	RFI Filter
Brake - Safe Stop	X	No brake chopper
LCP	G	Graphical Loc. Cont. Panel
Coating PCB	X	Not coated PCB
Mains Option	X	No Mains Option
Adaptation A	X	Standard Cable Entries
Adaptation B	X	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	X	Standard Language Pack
A Option	AX	No A Option
B Option	BX	No B Option
C0 Option MCO	CX	No C0 option
C1 Option	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product Detail | FC-302P75KT5E66H2XGXXXXXXXAXBXCXXXXDX

PRODUCT DETAILS

C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	C2	C2
Typecode Part 1		FC-302P75KT5E66H2XGX
Typecode Part 2		XXXXXXXXAXBXCXXXXDX
Product Catalog	GLBL	Global (Standard)
STAT NO		60035
Power 150% (HO) [KW]	75	75
Power 110% (NO) [KW]	90	90
Height [mm]	780,0	780,0
Width w/ no C options [mm]	370,0	370,0
Depth [mm]	332,0	332,0
Depth with Option A/B [mm]	332,0	332,0
kVA	102	102
Power Loss NO [W]	1474	1474
Power Loss NO [W]	1474	1474
Power Loss HO [W]	1232	1232
Power Loss HO [W]	1232	1232
Continuous Current (NO) [A]	177	177
Intermittent Current (NO) [A]	195	195
Continuous Current (NO) [A]	160	160
Intermittent Current (NO) [A]	176	176
Continuous Current (HO) [A]	147	147
Intermittent Current (HO) [A]	220	220
Continuous Current (HO) [A]	130	130
Intermittent Current (HO) [A]	195	195
Calculated Gross Weight [kg]		58.93
Calculated Package Weight		3.34
Calculated Net Weight [kg]		55.59
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Plant from Orderline	B901	B901
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-302P75KT5E66H2XGX
Modelcode02		XXXXXXXXAXBXCXXXXDX
Proposition 65		WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.