

Product Detail | FC-302PK55T2E55H2BGXXSXSSXXXAXBXXXXX



131X7322

FC-302PK55T2E55H2BGXXSXSSXXXAXBXXXXX

Frequency converter
FC-302PK55T2E55H2BGXXSXSSXXXAXBXXXXX
VLT® AutomationDrive FC-302
0.55 KW / 0.75 HP,
Three phase, 200 - 240 VAC, IP55 / Type 12
RFI Filter
Brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A5
No A Option, No B Option
No C1 option, No D option

Other options according to Model code

Model code: FC-302PK55T2E55H2BGXXSXSSXXXAXBXXXXX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

View Efficiency Data

PRODUCT DETAILS

Gross weight		10.926 Kilogram
Net weight		10.31 Kilogram
Volume		39.798 Liter
EAN		5710107265060
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® AutomationDrive FC-
Series	302	302
Power Rating	PK55	0.55 KW / 0.75 HP
Phase	T	Three phase
Mains Voltage	2	200 - 240 VAC
Enclosure	E55	IP55 / Type 12
RFI Filter	H2	RFI Filter
Brake - Safe Stop	B	Brake chopper
LCP	G	Graphical Loc. Cont. Panel
Coating PCB	X	Not coated PCB
Mains Option	X	No Mains Option
Adaptation A	S	Smooth imperial cable entr
Adaptation B	X	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	X	Standard Language Pack
A Option	AX	No A Option
B Option	BX	No B Option
C0 Option MCO	CX	No C0 option
C1 Option	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product Detail | FC-302PK55T2E55H2BGXXSX5XXXXAXBXXXXDX

PRODUCT DETAILS		
C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	A5	A5
Typecode Part 1		FC-302PK55T2E55H2BGX
Typecode Part 2		XSX5XXXXAXBXXXXDX
Product Catalog	NO_VIEW	NO VIEW
STAT NO		33035
Power 160% (HO) [KW]	0.55	0.55
Height [mm]	420,0	420,0
Width w/ no C options [mm]	242,0	242,0
Depth [mm]	200,0	200,0
Depth with Option A/B [mm]	200,0	200,0
kVA	1.26	1.26
Power Loss HO [W]	42	42
Continuous Current (HO) [A]	3.5	3.5
Intermittent Current (HO) [A]	5.6	5.6
Calculated Gross Weight [kg]		10.926
Calculated Package Weight		0.616
Calculated Net Weight [kg]		10.31
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-302PK55T2E55H2BGX
Modelcode02		XSX5XXXXAXBXXXXDX
Recommended Plant	ERR01	ERR01
Proposition 65		WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)