

Product Detail | FC-302P15KT6E21HXBGX3XXSXXXXAXBXXXXDX



134L3735

FC-302P15KT6E21HXBGX3XXSXXXXAXBXXXXDX

This product is not available in this store. Please contact your local [Customer Service Center](#).

[Customer Service Center](#)

Frequency converter

FC-302P15KT6E21HXBGX3XXSXXXXAXBXXXXDX

VLT® AutomationDrive FC-302

(P15K) 15 KW / 20 HP,

Three phase, 525 - 600 VAC, IP21 / Type 1

No RFI Filter

Brake chopper

Graphical Loc. Cont. Panel

Not coated PCB, Mains Disconnect + Fuse

Latest release std. SW.

Frame: B1

No A Option, No B Option

No C1 option, No D option

Other options according to Model code

Model code: FC-302P15KT6E21HXBGX3XXSXXXXAXBXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

[View Efficiency Data](#)

PRODUCT DETAILS

Gross weight		24.8 Kilogram
Net weight		21.18 Kilogram
Volume		158.268 Liter
EAN		5710107788989
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® AutomationDrive FC-
Series	302	302
Power Rating	P15K	(P15K) 15 KW / 20 HP
Phase	T	Three phase
Mains Voltage	6	525 - 600 VAC
Enclosure	E21	IP21 / Type 1
RFI Filter	HX	No RFI Filter
Brake - Safe Stop	B	Brake chopper
LCP	G	Graphical Loc. Cont. Panel
Coating PCB	X	Not coated PCB
Mains Option	3	Mains Disconnect + Fuse
Adaptation A	X	Standard Cable Entries
Adaptation B	X	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	X	Standard Language Pack

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product Detail | FC-302P15KT6E21HXBGX3XXSXXXXAXBXXXXDX

PRODUCT DETAILS

A Option	AX	No A Option
B Option	BX	No B Option
C0 Option MCO	CX	No C0 option
C1 Option	X	No C1 option
C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	B1	B1
Typecode Part 1		FC-302P15KT6E21HXBGX
Typecode Part 2		3XXSXXXXAXBXXXXDX
Product Catalog	NO_VIEW	NO VIEW
STAT NO		60062
Power 160% (HO) [KW]	15	15
Power 110% (NO) [KW]	18.5	18.5
Height [mm]	494,0	494,0
Width w/ no C options [mm]	243,0	243,0
Depth [mm]	261,0	261,0
Depth with Option A/B [mm]	261,0	261,0
kVA	21.9	21.9
Power Loss NO [W]	370	370
Power Loss NO [W]	370	370
Power Loss HO [W]	300	300
Power Loss HO [W]	300	300
Continuous Current (NO) [A]	28	28
Intermittent Current (NO) [A]	30.8	30.8
Continuous Current (NO) [A]	27	27
Intermittent Current (NO) [A]	29.7	29.7
Continuous Current (HO) [A]	23	23
Intermittent Current (HO) [A]	36.8	36.8
Continuous Current (HO) [A]	22	22
Intermittent Current (HO) [A]	35.2	35.2
Calculated Gross Weight [kg]		24.8
Calculated Package Weight		3.62
Calculated Net Weight [kg]		21.18
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-302P15KT6E21HXBGX
Modelcode02		3XXSXXXXAXBXXXXDX
Recommended Plant	ERR01	ERR01
Proposition 65		WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.