Product Specifications



1/2" x 2-3/4" Wedge Anchor

Part Number W12234 Category Number 4540 UPC 781002593126

Wedge Anchors are manufactured with a carbon steel body and expansion clip, and are designed for normal and lightweight concrete. These fully threaded expanding anchors are ICC-ESR listed for seismic zones, cracked, and uncracked concrete. They feature a pilot on the hammered end to prevent first thread damage and are a non-bottom-bearing anchor. Common applications for use include structural connections, cable trays, strut, fire sprinklers, and piping supports in concrete substrate. For installation instructions and weight loads, reference the technical data sheet.



Physical Characteristics

Fully UNC 1/2" x 2-3/4"
1/2" v 2-3/4"
1/2 X Z=3/4
1/2"
2-3/4"
1-3/8"
13
1/2"-13
Carbon Steel
Zinc Plated

Packaging Details

Included	Washer & Nut
Standard Qty	50
Master Qty	200
Price Per	100
Package Length	8.40
Package Width	5.90
Package Height	3.90
Net Weight	0.1945
Package Weight	9.73

Performance Data

Pre-Drill Size	1/2"
Minimum Embedment Depth	2-1/2"
Applications	Normal and Lightweight Concrete, Seismic Zones, Crack and Uncracked Concrete
Special Features	Carbon Steel Body, Expansion Clip, Pilot End to Prevent First Thread Damage When Installing
Cement Type	Various PSI

Certifications

Meets/Exceeds	ICC APPROVAL ESR-3932
RoHS Compliant	Yes

L.H. Dottie Co. Commerce, CA 323-725-1000 www.lhdottie.com