

Eaton B29SRE45BX3E032

Catalog Number: B29SRE45BX3E032

Eaton definite purpose 1-phase starter, Non-reversing w/ C396, Separate ctrl, Open w/ DIN rail mount adapter, Lugs w/o quick connect terms, 45 A, 208/240 V coil, No side aux contacts, Std. C396 OLR, 24-32 A overload

General specifications

Product Name	Catalog Number
Eaton definite purpose starter	B29SRE45BX3E032
UPC	Product Length/Depth
786685210421	6.67 in
Product Height	Product Width
13.27 in	7.64 in
Product Weight	Warranty
10.6 lb	1 year
Certifications	
UL Listed	
CSA Certified	



Product specifications

Contact configuration

No side mounting auxiliary contacts

Inductive full load

45 A

Overload range

24-32 A

Phase

Single-phase

OLr model designation

Std. C396 OLR

Control characteristics

Separate control

Enclosure

Open with DIN rail mounting adapter

Amperage Rating

208-240 V, 50/60 Hz

Coil

208/240 Vac

Type

Non-reversing w/ C396

Model

Starter

Terminals

Lugs without quick connect terms

Current range

45 A

Resources

Catalogs

[Lighting and Definite Purpose Control](#)

Specifications and datasheets

[Eaton Specification Sheet - B29SRE45BX3E032](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)