

Eaton P48G11B1530CUB

Catalog Number: P48G11B1530CUB

15 kVA Mini-Power Center 1PH 480 V-120/240 V, NEMA 3R, 80°C rise, 310, M48G11HB, Copper, 30 spaces, bolt-on



General specifications

Product Name	Catalog Number
Eaton Mini-Power center	P48G11B1530CUB
UPC	Product Length/Depth
786680240676	14.58 in
Product Height	Product Width
43.37 in	20.41 in
Product Weight	Compliances
1.1 lb	NAFTA
Certifications	
UL Listed	
ANSI	
IEEE Certified	
CSA Certified	

Physical Attributes

Coil material

Copper

Enclosure

NEMA 3R

Frame

310

Insulation

180 °C

Mounting

Wall Mount

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

M48G11HB

Performance Ratings

Frequency rating

60 Hz

kVA

15 kVA

Kva Rating

15 kVA

Phase

Single-phase

Primary voltage

480 V

Secondary Voltage

120/240 V

Sound Level

NEMA ST-20

Temperature rise

80 °C rise

Volt ampere rating

15 kVA

Miscellaneous

Modification 1

NEMA 3R

Weathershield

Not required

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P48G11B1530CUB](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)