

# Eaton P48G11S0718HCUB

Catalog Number: P48G11S0718HCUB

7.5 kVA Mini Power Center 1PH 480-120/240, 115C Rise, Copper Windings, Copper bolt-on interior, NEMA 3R, 18 branch spaces, HFD Primary Main breaker



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Mini-Power center	P48G11S0718HCUB
<b>UPC</b>	<b>Product Length/Depth</b>
786680235610	9.66 in
<b>Product Height</b>	<b>Product Width</b>
32.9 in	12.56 in
<b>Product Weight</b>	<b>Compliances</b>
178 lb	NAFTA
<b>Certifications</b>	
ANSI	
UL Listed	
CSA Certified	
IEEE Certified	

## Physical Attributes

### Coil material

Copper

### Enclosure

NEMA 3R

### Frame

307

### Insulation

180 °C

### Mounting

Wall Mount

### Tap size

2 at -5% FCBN

### Type

Mini-power center

### Wiring connection

M48G11EB

## Performance Ratings

### Frequency rating

60 Hz

### kVA

7.5 kVA

### Kva Rating

7.50 kVA

### Phase

Single-phase

### Primary voltage

480 V

### Secondary Voltage

120/240 V

### Sound Level

NEMA ST-20

### Temperature rise

115 °C rise

### Volt ampere rating

7.5 kVA

## Miscellaneous

### Modification 1

HFD primary main

### Weathershield

Not required

## Resources

### Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

### Multimedia

[Eaton's Transformer Flex Center](#)

### Specifications and datasheets

[Eaton Specification Sheet - P48G11S0718HCUB](#)

### Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)