

Eaton P48G11S1024CCUBS6

Catalog Number: P48G11S1024CCUBS6

10 kVA Mini Power Center 1PH 480-120/240, 115C Rise, Copper Windings, Copper bolt-on interior, NEMA 3R 316 Stainless steel enclosure, 24 branch spaces, FDC Primary Main breaker



General specifications

Product Name	Catalog Number
Eaton Mini-Power center	P48G11S1024CCUBS6
UPC	Product Length/Depth
786680235061	11.82 in
Product Height	Product Width
39.67 in	14.97 in
Product Weight	Compliances
368 lb	NAFTA
Certifications	
UL Listed	
IEEE Certified	
CSA Certified	
ANSI	

Physical Attributes

Coil material

Copper

Enclosure

NEMA 3R

Frame

309

Insulation

180 °C

Mounting

Wall Mount

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

M48G11GB

Performance Ratings

Frequency rating

60 Hz

kVA

10 kVA

Kva Rating

10 kVA

Phase

Single-phase

Primary voltage

480 V

Secondary Voltage

120/240 V

Sound Level

NEMA ST-20

Temperature rise

115 °C rise

Volt ampere rating

10 kVA

Miscellaneous

Modification 1

FDC primary main

Weathershield

Not required

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P48G11S1024CCUBS6](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)