

# Eaton P48G11S1024HCUB

Catalog Number: P48G11S1024HCUB

10 kVA Mini-Power Center 1PH 480 V-120/240 V, NEMA 3R, 115°C rise, 309, M48G11GB, Copper, 24 spaces, bolt-on, HFD main



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Mini-Power center	P48G11S1024HCUB
<b>UPC</b>	<b>Product Length/Depth</b>
786680240775	11.82 in
<b>Product Height</b>	<b>Product Width</b>
43.91 in	14.97 in
<b>Product Weight</b>	<b>Compliances</b>
377 lb	NAFTA
<b>Certifications</b>	
IEEE Certified	
CSA Certified	
ANSI	
UL Listed	

## Physical Attributes

### Coil material

Copper

### Enclosure

NEMA 3R

### Frame

309

### Insulation

180 °C

### Mounting

Wall Mount

### Tap size

2 at -5% FCBN

### Type

Mini-power center

### Wiring connection

M48G11GB

## Performance Ratings

### Frequency rating

60 Hz

### kVA

10 kVA

### Kva Rating

10 kVA

### Phase

Single-phase

### Primary voltage

480 V

### Secondary Voltage

120/240 V

### Sound Level

NEMA ST-20

### Temperature rise

115 °C rise

### Volt ampere rating

10 kVA

## Miscellaneous

### Modification 1

NEMA 3R

### Weathershield

Not required

## Resources

### Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

### Multimedia

[Eaton's Transformer Flex Center](#)

### Specifications and datasheets

[Eaton Specification Sheet - P48G11S1024HCUB](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)