

Eaton P60G28T3024

Catalog Number: P60G28T3024

30 KVA Mini Power Center 3PH 600V Delta-208Y/120V 24 spaces

General specifications

Product Name	Catalog Number
Eaton Mini-Power center	P60G28T3024
UPC	Product Length/Depth
786680225857	13.62 in
Product Height	Product Width
40.01 in	32.63 in
Product Weight	Warranty
635 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
NAFTA	CSA Certified ANSI IEEE Certified UL Listed



Physical Attributes

Coil material

Aluminum

Enclosure

NEMA 3R

Frame

291B

Insulation

180 °C

Mounting

Wall Mount

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

M60G1L

Performance Ratings

Frequency rating

60 Hz

kVA

30 kVA

Kva Rating

30 kVA

Phase

Three-phase

Primary voltage

600 V

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

115 °C rise

Volt ampere rating

30 kVA

Miscellaneous

Modification 1

NEMA 3R

Weathershield

Not required

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P60G28T3024](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)