

# Eaton TRL04

Catalog Number: TRL04

Eaton 4-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton TR timing relay	TRL04
<b>UPC</b>	<b>Product Length/Depth</b>
786685313573	1.3 in
<b>Product Height</b>	<b>Product Width</b>
3.43 in	1.8 in
<b>Product Weight</b>	<b>Warranty</b>
.09 lb	1 year Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>Compliances</b>	<b>Certifications</b>
CE Marked TUV	CSA Certified cULus Listed



## Product specifications

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Series

TR

### Input voltage

24-240 Vac/dc

### Frequency rating

50-60 Hz

### Functions

ON/OFF delay

Power triggered

Single shot leading edge voltage controlled

Flasher-pause first

### Enclosure

IP40

### Time delay

0.05 seconds-100 hours

### Mounting method

Compact DIN rail

## Resources

### Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions

### Installation instructions

TRL04 and TRL07 Installation Instructions

### Specifications and datasheets

Eaton Specification Sheet - TRL04



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia