

# Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton TR timing relay	TRL07
<b>UPC</b>	<b>Product Length/Depth</b>
786685313580	2.56 in
<b>Product Height</b>	<b>Product Width</b>
3.43 in	.69 in
<b>Product Weight</b>	<b>Warranty</b>
.16 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>Compliances</b>	<b>Certifications</b>
TUV CE Marked	cULus Listed CSA Certified



## Product specifications

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Series

TR

### Input voltage

24-240 Vac/dc

### Frequency rating

50-60 Hz

### Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

### Enclosure

IP40

### Time delay

0.05 seconds-100 hours

### Mounting method

Compact DIN rail

## Resources

### Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions

### Installation instructions

TRL04 and TRL07 Installation Instructions

### Specifications and datasheets

Eaton Specification Sheet - TRL07



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia