Product specifications

Eaton TRL27

Catalog Number: TRL27

Eaton 7-function universal TR series timing relay, style terminals, 0.05 seconds-100 hours time delay, 12-240 Vac/dc input voltage, Compact DIN rail mount, DPDT contact configuration, IP40 enclosure

General specifications

Product Name Catalog Number

Eaton TR timing relay TRL27

UPC Product Length/Depth

786685313597 2.56 in

Product Height Product Width

3.43 in 1.38 in

Product Weight Warranty

.24 lb Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Compliances Certifications

CE Marked TUV CSA Certified cULus Listed



Product specifications

Enclosure material

Self-extinguishing plastic

Contact configuration

DPDT

Series

TR

Input voltage

12-240 Vac/dc

Frequency rating

50-60 Hz

Functions

ON/OFF delay

Single shot leading or trailing edge voltage controlled and control

input

Power triggered

Trailing edge OFF

ON delay control signal start

Flasher-pause first

Enclosure

IP40

Time delay

0.05 seconds-100 hours

Mounting method

Compact DIN rail

Resources

Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity

Solutions

Installation instructions

TRL27 Installation Instructions

Specifications and datasheets

Eaton Specification Sheet - TRL27



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia