



XG2-12-2B

XG2-12-2BW



XG2-12-2W



XG2-12-2TT



XG2-14-2S

NEMA TYPE 4X & 6P Enclosure:

- Excels in demanding outdoor & in-plant environments
- Provides added protection against ground fault shock hazards in high-risk areas
- Resists hose-directed water

Custom configurations are available for your jobsite or OEM applications. Contact your nearest representative or the factory today!

FEATURES:

- cULus Listed
- Meets NEC & OSHA construction site requirements
- Fully sealed, NEMA type 4X and 6P submersible GFCI body
- 4X and 6P submersible configurations available with Perma-Tite® 2 plug/connector
- Circuit conforms to the UL 943 standard for safety governing GFCIs
- A more stringent voltage surge test ensures the GFCI can handle higher surge current
- Corrosion test ensures greater immunity to damp, corrosive environments
- Enhanced immunity to conducted radio frequency noise reduces nuisance trips
- Works on two-wire or three-wire circuits
- Available in 15A & 20A models
- Up to 1.5 horse-power switch rating
- Available with factory-wired & molded-on devices
- Engineered strain relief protects cord from excessive bending & pulling
- Test & Reset buttons clearly marked for easy identification & recessed to prevent accidental activation
- Automatic & manual power-up models are available
- A wide variety of outlets are available; from molded-on single connector & Tri-Tap™ to Perma-Tite2® devices & Ericson outlet boxes
- Oversized test & reset buttons are easier to operate and provide enhanced tactile feel & audible feedback



XG2 Series Selection Guide

Cat. Number	POWER UP TYPE	LENGTH	PLUG	CONNECTOR	AMPS	WATTS
With Molded-On Plug & Connector						
XG2-14-2S	AUTO	2	MLD 5-15	MLD 5-15	15	1875
XG2-14-25S		25		MLD 5-15		
XG2-12-2TT		2		MLD 5-15 TRI		
XG2-12-50TT		50		MLD 5-15 TRI		
With Factory-Wired Perma-Grip™ Plug & Connector or Molded Plug						
XG2-12-2G	AUTO	2	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-2G-15	AUTO	2	MLD 5-15	5-15 1610-CG	15	1875
XG2-12-2G-MR-15	MANUAL	2	MLD 5-15	5-15 1610-CG	15	1875
XG2-12-2G-LKG	AUTO	2	5-20 2310-PG	5-20 2410-CG	20	2500
XG2-12-2G-MR-LKG	MANUAL	2	5-20 2310-PG	5-20 2410-CG	20	2500
XG2-12-2G-MR	MANUAL	2	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-10G	AUTO	10	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-10G-MR	MANUAL	10	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-25G	AUTO	25	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-25G-15	AUTO	25	MLD 5-15	5-15 1610-CG	15	1875
XG2-12-25G-MR-15	MANUAL	25	MLD 5-15	5-15 1610-CG	15	1875
XG2-12-25G-LKG	AUTO	25	5-20 2310-PG	5-20 2410-CG	20	2500
XG2-12-25G-MR-LKG	MANUAL	25	5-20 2310-PG	5-20 2410-CG	20	2500
XG2-12-25G-MR	MANUAL	25	5-20 1512-PG	5-20 1612-CG	20	2500
XG2-12-50G	AUTO	50	5-20 1512-PG	5-20 1612-CG	20	2500
With Factory-Wired Perma-Tite® Plug & Connector						
XG2-12-2W	AUTO	2	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-2W-15	AUTO	2	5-15 1510-PW6P	5-15 1610-CW6P	15	1875
XG2-12-2W-MR-15	MANUAL	2	5-15 1510-PW6P	5-15 1610-CW6P	15	1875
XG2-12-2W-LKG	AUTO	2	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-2W-MR-LKG	MANUAL	2	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-2W-MR	MANUAL	2	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-10W	AUTO	10	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-10W-MR	MANUAL	10	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-10W-MR-15	MANUAL	10	5-15 1510-PW6P	5-15 1610-CW6P	15	1875
XG2-12-10W-LKG	AUTO	10	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-10W-MR-LKG	MANUAL	10	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-25W	AUTO	25	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-25W-15	AUTO	25	5-15 1510-PW6P	5-15 1610-CW6P	15	1875
XG2-12-25W-MR-15	MANUAL	25	5-15 1510-PW6P	5-15 1610-CW6P	15	1875
XG2-12-25W-LKG	AUTO	25	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-25W-MR-LKG	MANUAL	25	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-25W-MR	MANUAL	25	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-50W	AUTO	50	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-50W-MR	MANUAL	50	5-20 1512-PW6P	5-20 1612-CW6P	20	2500
XG2-12-50W-LKG	AUTO	50	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500
XG2-12-50W-MR-LKG	MANUAL	50	L5-20 2310-PW6P	L5-20 2410-CW6P	20	2500

Notes: 1. All cord is SJT. 2. All product is rated 120 volts.

XG2-14-2S

XG2-12-2TT

XG2-12-2G

XG2-12-2G-15

XG2-12-2W

6P
SUBMERSIBLE

**All "W" Models
Have Perma-Tite®
Water Tight
Plugs & Connectors**

UL LISTED

SWITCH RATED
UP TO 15MP

6P SUBMERSIBLE

4X

Assembled in the USA

XG2 Series Selection Guide

Cat. Number	POWER UP TYPE	LENGTH	PLUG	CONNECTOR	AMPS	WATTS
With Molded-On Plug & Connector						
With Factory-Wired 6000 Box, Two Duplex Receptacles & Perma-Grip™ Plug or Molded Plug						
XG2-12-2B	AUTO	2	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-2B-15	AUTO	2	MLD 5-15	(2) 5-15 DUPLX	15	1875
XG2-12-2B-MR-15	MANUAL	2	MLD 5-15	(2) 5-15 DUPLX	15	1875
XG2-12-2B-MR	MANUAL	2	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-10B	AUTO	10	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-10B-MR	MANUAL	10	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-25B	AUTO	25	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-25B-15	AUTO	25	MLD 5-15	(2) 5-15 DUPLX	15	1875
XG2-12-25B-MR-15	MANUAL	25	MLD 5-15	(2) 5-15 DUPLX	15	1875
XG2-12-25B-MR	MANUAL	25	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-50B	AUTO	50	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-50B-MR	MANUAL	50	5-20 1512-PG	(2) 5-20 DUPLX	20	2500
XG2-12-50B-15	AUTO	50	MLD 5-15	(2) 5-15 DUPLX	15	1875
XG2-12-50B-MR-15	MANUAL	50	MLD 5-15	(2) 5-15 DUPLX	15	1875
With Factory-Wired 6100 Box, Two Duplex Receptacles & Perma-Tite® Plug						
XG2-12-2BW	AUTO	2	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-2BW-15	AUTO	2	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
XG2-12-2BW-MR-15	MANUAL	2	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
XG2-12-2BW-MR	MANUAL	2	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-10BW	AUTO	10	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-10BW-MR	MANUAL	10	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-25BW	AUTO	25	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-25BW-15	AUTO	25	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
XG2-12-25BW-MR-15	MANUAL	25	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
XG2-12-25BW-MR	MANUAL	25	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-50BW	AUTO	50	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-50BW-MR	MANUAL	50	5-20 1512-PW6P	(2) 5-20 DUPLX	20	2500
XG2-12-50BW-15	AUTO	50	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
XG2-12-50BW-MR-15	MANUAL	50	5-15 1510-PW6P	(2) 5-15 DUPLX	15	1875
Molded Plug with blunt end for equipment wiring						
XG2R-12-2BS-15		2				
XG2R-12-10BS-15		10				
XG2R-12-25BS-15	AUTO	25	MLD5-15	BLUNT	15*	1875
XG2R-12-50BS-15		50			*Due to plug rating Plug can be removed. Unit rated for 20A max.	

NOTES: XG2 models with blunt end are UL & cUL recognized.

