




Product information BAT-Controller WLC50

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC50

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49859-24497-118024-144715/en/conf/uisstate>

| | |
|---|---|
| Name | BAT-Controller WLC50 |
| |  |
| | Central Firmware deployment and management of the Access Points. Requires an external web server. |
| Delivery informations | |
| Availability | available |
| Product description | |
| Description | Central Firmware deployment and management of the Access Points. Requires an external web server. |
| Port type and quantity | 4 individual Ethernet ports 10/100/1000 Mbps |
| Type | BAT-Controller WLC50 |
| Order No. | 942 034-002 |
| Managed Access Points | 50 |
| More Interfaces | |
| Power supply/signaling contact | Internal power supply unit (110–230 V, 50-60 Hz) |
| Hardware requirements | |
| Network | OpenBAT, BAT54 and BAT300 access points |
| Mechanical construction | |
| Housing | Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front |
| Ambient conditions | |
| Operating temperature | 5 °C ... 40 °C |
| Relative humidity (non-condensing) | 0 % ... 95 % |
| Dimensions (W x H x D) | 435 x 45 x 207 mm |
| Weight | 3800 g |
| Scope of delivery and accessories | |
| Scope of delivery | CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter |

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.

