




## Product information BAT-Controller WLC100

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC100	
<a href="http://www.e-catalog.beldensolutions.com/link/57078-24455-49859-24497-118024-144714/en/conf/ui/state">http://www.e-catalog.beldensolutions.com/link/57078-24455-49859-24497-118024-144714/en/conf/ui/state</a>	
Name	BAT-Controller WLC100
	
	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Central Firmware deployment and management of the Access Points. Requires an external web server.
Port type and quantity	4 individual Ethernet ports 10/100/1000 Mbps
Type	BAT-Controller WLC100
Order No.	942 034-003
Managed Access Points	100
<b>More Interfaces</b>	
Power supply/signaling contact	Internal power supply unit (110–230 V, 50-60 Hz)
<b>Hardware requirements</b>	
Network	OpenBAT, BAT54 and BAT300 access points
<b>Mechanical construction</b>	
Housing	Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front
<b>Ambient conditions</b>	
Operating temperature	5 °C ... 40 °C
Relative humidity (non-condensing)	0 % ... 95 %
Dimensions (W x H x D)	435 x 45 x 207 mm
Weight	3800 g
<b>Scope of delivery and accessories</b>	
Scope of delivery	CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.

