




## Product information Fast Ethernet MICE Media Modules, IO - MM24- IOIOIOIOEZHH

Industrial Ethernet:Modular Industrial Switches:Configurable media modules:Fast Ethernet MICE media modules, digital IO :Fast Ethernet MICE Media Modules, IO

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49860-67478-176541-176542/en/MM24-IOIOIOIOEZHH/uistate>

Name	Fast Ethernet MICE Media Modules, IO
	
	Fast Ethernet media module for MICE Switches (MS...) with 4 digital inputs and 4 digital outputs to transmit status signals, modul needs at least SW7.0 Layer 2 Professional
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Fast Ethernet media module for MICE Switches (MS...) with 4 digital inputs and 4 digital outputs to transmit status signals, modul needs at least SW7.0 Layer 2 Professional
Port type and quantity	Port 1: 1 x digital input, 1 x digital output; Port 2: 1 x digital input, 1 x digital output; Port 3: 1 x digital input, 1 x digital output; Port 4: 1 x digital input, 1 x digital output
Type	MM24-IOIOIOIOEZHH
Order No.	MM24-IOIOIOIOEZHH
<b>Power requirements</b>	
Operating voltage	Power supply via the backplane of the MICE switch
Power consumption	7.5 W
<b>Ambient conditions</b>	
Operating temperature	-40 °C ... 70 °C
Storage/transport temperature	-40 °C ... 70 °C
Protective paint on PCB	Yes (conformal coating)
Relative humidity (non-condensing)	10 % ... 95 %
<b>Mechanical construction</b>	
Dimensions (W x H x D)	38 mm x 134 mm x 118 mm
Width	38 mm
Height	134 mm
Depth	118 mm
Mounting	Backplane
Weight	n/a
Protection class	IP20
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3.5 mm, 5–8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4–150 Hz, 10 cycles, 1 octave/min
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 1 kV (line/earth), 0.5 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
<b>Scope of delivery and accessories</b>	
Scope of delivery	Module, operating manual
Accessories to order separately	ML-MS2/MM labels



**HIRSCHMANN**

A **BELDEN** BRAND

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.