

MODULAR SINGLE DOOR, MCS



The mild steel single door combinable floor standing enclosure range, MCS, with a IP 55 protection degree, is available off the shelf in many different sizes. This enclosure range is well suited for many different applications. The risk for component failure, and with that unnecessary downtime, is eliminated as water and dust are prevented from entering the enclosure.

INDUSTRY STANDARDS

UL 508A Listed; Type 12; File No. E61997

cUL Listed per CSA C22.2 No.0, No.0.4, No.14, No.94; Type 12; File No. E61997

NEMA/EEMAC Type 12

CSA, File No. 1442951: Type 12

IEC 62208 IP55

KEMA, GOST, DNV, CE, EAC

FEATURES

Material: Frame: 1.5 mm painted steel. Door: 2 mm painted steel. Rear, roof and side panels: 1.5 mm painted steel. Mounting plate: 3 mm galvanized steel. Bottom plates: 1 mm galvanized steel.

Frame: Seam welded reversed open profiles with 25 mm hole pattern, according to DIN 43660. Including integrated external hole pattern.

Door: Mounted with four hinges allowing left or right hand opening. Including door frame with 25 mm hole pattern.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting. RD version comes with rear door instead of rear panel.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit lock with 3 mm insert. Standard inserts, cylinders, lift handles and T-handles are available as accessories.

Bottom plates: Consists of three or four (D>600) pieces.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm, with the MPD02 accessory. Supplied, attached on the outside of the enclosure packaging.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP 55 | TYPE 12 | IK 10.

Mounting requirements: Standard delivery ready for combined installation. For stand-alone installation add side panels.

Delivery: Frame with fitted door, rear panel, roof panel, bottom plates, mounting plate (not included for PER5 version) and door frame. For 400 mm wide enclosures, a mounting plate, bottom plates and door frame are not included. For enclosures 2200 mm height, delivery includes two CMB profiles mounted in depth. Delivery also includes earthing bolts. Delivered on a pallet which is identical to the width of the enclosure to allow baying without removal. All packing material is recyclable.

SPECIFICATIONS

Body Thickness:	1.5 mm
Door Thickness:	2 mm
Color:	Light Gray
Material:	Mild Steel
Finish:	Powder Coated
Color Code:	RAL 7035

Table 1/1

Catalog Number	Height	Width	Depth	Mounting Plate Included	Door/Rear Panel	Max Mounting Depth
MCS18044R5	1800 mm	400 mm	400 mm	No	Rear panel	
MCS18045R5	1800 mm	400 mm	500 mm	No	Rear panel	
MCS18046R5	1800 mm	400 mm	600 mm	No	Rear panel	
MCS18055PER5	1800 mm	500 mm	500 mm	No	Rear panel	
MCS18055R5	1800 mm	500 mm	500 mm	Yes	Rear panel	459 mm
MCS18064PER5	1800 mm	600 mm	400 mm	No	Rear panel	
MCS18064R5	1800 mm	600 mm	400 mm	Yes	Rear panel	359 mm
MCS18065PER5	1800 mm	600 mm	500 mm	No	Rear panel	
MCS18065R5	1800 mm	600 mm	500 mm	Yes	Rear panel	459 mm
MCS18066PER5	1800 mm	600 mm	600 mm	No	Rear panel	
MCS18066R5	1800 mm	600 mm	600 mm	Yes	Rear panel	559 mm
MCS18084PER5	1800 mm	800 mm	400 mm	No	Rear panel	
MCS18084R5	1800 mm	800 mm	400 mm	Yes	Rear panel	359 mm
MCS18085PER5	1800 mm	800 mm	500 mm	No	Rear panel	
MCS18085R5	1800 mm	800 mm	500 mm	Yes	Rear panel	459 mm
MCS18086PER5	1800 mm	800 mm	600 mm	No	Rear panel	
MCS18086R5	1800 mm	800 mm	600 mm	Yes	Rear panel	559 mm
MCS18088R5	1800 mm	800 mm	800 mm	Yes	Rear panel	
MCS18104PER5	1800 mm	1000 mm	400 mm	No	Rear panel	
MCS18104R5	1800 mm	1000 mm	400 mm	Yes	Rear panel	359 mm
MCS18105PER5	1800 mm	1000 mm	500 mm	No	Rear panel	
MCS18105R5	1800 mm	1000 mm	500 mm	Yes	Rear panel	459 mm
MCS18106PER5	1800 mm	1000 mm	600 mm	No	Rear panel	
MCS18106R5	1800 mm	1000 mm	600 mm	Yes	Rear panel	559 mm
MCS20044R5	2000 mm	400 mm	400 mm	No	Rear panel	
MCS20045R5	2000 mm	400 mm	500 mm	No	Rear panel	
MCS20046R5	2000 mm	400 mm	600 mm	No	Rear panel	
MCS20048R5	2000 mm	400 mm	800 mm	No	Rear panel	
MCS20055PER5	2000 mm	500 mm	500 mm	No	Rear panel	
MCS20055R5	2000 mm	500 mm	500 mm	Yes	Rear panel	459 mm
MCS20064PER5	2000 mm	600 mm	400 mm	No	Rear panel	
MCS20064R5	2000 mm	600 mm	400 mm	Yes	Rear panel	359 mm
MCS20065PER5	2000 mm	600 mm	500 mm	No	Rear panel	

CatalogNumber	Height	Width	Depth	Mounting Plate Included	Door/RearPanel	Max Mounting Depth
MCS20065R5	2000 mm	600 mm	500 mm	Yes	Rear panel	459 mm
MCS20066PER5	2000 mm	600 mm	600 mm	No	Rear panel	
MCS20066R5	2000 mm	600 mm	600 mm	Yes	Rear panel	559 mm
MCS20068PER5	2000 mm	600 mm	800 mm	No	Rear panel	
MCS20068PERDR5	2000 mm	600 mm	800 mm	Yes	Rear door	
MCS20068R5	2000 mm	600 mm	800 mm	Yes	Rear panel	759 mm
MCS20068RDR5	2000 mm	600 mm	800 mm	Yes	Rear door	
MCS200810PERDR5	2000 mm	800 mm	1000 mm	Yes	Rear door	
MCS200810RDR5	2000 mm	800 mm	1000 mm	Yes	Rear door	
MCS20084PER5	2000 mm	800 mm	400 mm	No	Rear panel	
MCS20084R5	2000 mm	800 mm	400 mm	Yes	Rear panel	359 mm
MCS20085PER5	2000 mm	800 mm	500 mm	No	Rear panel	
MCS20085R5	2000 mm	800 mm	500 mm	Yes	Rear panel	459 mm
MCS20086PER5	2000 mm	800 mm	600 mm	No	Rear panel	
MCS20086PERDR5	2000 mm	800 mm	600 mm	Yes	Rear door	
MCS20086R5	2000 mm	800 mm	600 mm	Yes	Rear panel	559 mm
MCS20086RDR5	2000 mm	800 mm	600 mm	Yes	Rear door	
MCS20088PER5	2000 mm	800 mm	800 mm	No	Rear panel	
MCS20088PERDR5	2000 mm	800 mm	800 mm	Yes	Rear door	
MCS20088R5	2000 mm	800 mm	800 mm	Yes	Rear panel	759 mm
MCS20088RDR5	2000 mm	800 mm	800 mm	Yes	Rear door	
MCS20104PER5	2000 mm	1000 mm	400 mm	No	Rear panel	
MCS20104R5	2000 mm	1000 mm	400 mm	Yes	Rear panel	359 mm
MCS20105PER5	2000 mm	1000 mm	500 mm	No	Rear panel	
MCS20105R5	2000 mm	1000 mm	500 mm	Yes	Rear panel	459 mm
MCS20106PER5	2000 mm	1000 mm	600 mm	No	Rear panel	
MCS20106R5	2000 mm	1000 mm	600 mm	Yes	Rear panel	559 mm
MCS20108PER5	2000 mm	1000 mm	800 mm	No	Rear panel	
MCS20108PERDR5	2000 mm	1000 mm	800 mm	Yes	Rear door	
MCS20108R5	2000 mm	1000 mm	800 mm	Yes	Rear panel	759 mm
MCS20108RDR5	2000 mm	1000 mm	800 mm	Yes	Rear door	
MCS22066PER5	2200 mm	600 mm	600 mm	No	Rear panel	
MCS22066R5	2200 mm	600 mm	600 mm	Yes	Rear panel	559 mm
MCS22068PER5	2200 mm	600 mm	800 mm	No	Rear panel	
MCS22068R5	2200 mm	600 mm	800 mm	Yes	Rear panel	759 mm
MCS22086PER5	2200 mm	800 mm	600 mm	No	Rear panel	
MCS22086R5	2200 mm	800 mm	600 mm	Yes	Rear panel	559 mm
MCS22088PER5	2200 mm	800 mm	800 mm	No	Rear panel	
MCS22088R5	2200 mm	800 mm	800 mm	Yes	Rear panel	759 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER