

## EXTREME ENCLOSURE GASKET REPLACEMENT KIT EPDM



This is replacement gasket for WXD bulletin Extreme Environments Enclosures. The gasket is easily removed and replaced if damaged. EPDM material is great for most industrial and outdoor applications with a temperature range of -50 to 120C (-58 to 248F)

### INDUSTRY STANDARDS

---

UL 508A Recognized; Type 3R, 4, 4X File No. E61997

cUL Recognized per CSA C22.2 No 94; Type 3R, 4, 4X File No. E61997

UL and cUL Classified to IEC 60529, IP66, IP69; File No. E503705

NEMA/EEMAC Type 3R, 4, 4X

ISO 20653, IP69k

IEC 60529, IP66, IP69

Meets NEMA Type 3RX requirements

### FEATURES

---

Gasket is easily removed and replaced if damaged

For most industrial and outdoor applications

Temperature range of -50 to 120C (-58 to 248F)

## SPECIFICATIONS

Table 1/1

Catalog Number	Article Number	Length	Fits Enclosure	Material	Finish	Color
<a href="#">XDGSKTKIT56E</a>	56983	46.14 in	16x12 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT64E</a>	56984	54.13 in	16x16 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT72E</a>	56985	62.13 in	16x20 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT80E</a>	56986	70.16 in	20x20 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT88E</a>	56987	78.15 in	20x24, 24x16 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT96E</a>	56988	86.14 in	24x24 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT108E</a>	56991	98.15 in	30x24 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT120E</a>	56992	110.16 in	30x30, 36x24 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT132E</a>	56993	122.13 in	36x30 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT144E</a>	56994	134.13 in	36x36, 42x30 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT156E</a>	56995	146.14 in	42x36 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT168E</a>	56996	158.15 in	48x36 in	EPDM	Smooth Matte	Black
<a href="#">XDGSKTKIT192E</a>	56997	182.13 in	60x36 in	EPDM	Smooth Matte	Black

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:  
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**