



SKU: BRBR-14-14-P50

UPC: 0783669200942

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Range 14-16, 1/4in Bolt Size, Non-insulated, Blue Color Code, Pack of 50

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	D1322
Installation Tooling	ILST-22K
Installing Dies	Die Set D1322
Insulation Flared End	No
Insulation Grip	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.177
Weight (LB)	0.2186
Weight BX (LB)	13.1182
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General

Bag Quantity	50
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3

UPC Code

78366920094

Bolt and Screw Sizes

Mounting Bolt/Stud Size

1/4

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

20U0

UL / CULUS Specification

UL/cUL 486A/B Listed

UL File Number

E6207

Color

Color

Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

14 Sol - 16 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

14 Str - 16 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Environment and Temperature

Halogen Free

NA

Temperature Rating

NA