

K

## TYPE DE-OX®

ILSCO Oxide inhibitor is available in three different formulas: NON-GRIT, ZINC, COPPER. Oxide Inhibitor is applied to the connector prior to inserting the wire conductor, providing an air-tight seal around the conductor, preventing oxides from forming. All three formulas are available in a variety of package sizes.

- NON-GRIT - ILSCO DE-OX series is suitable for aluminum or copper terminations.
- ZINC - ILSCO DE-OX-Z series contains flecks of zinc providing improved pull-out strength and reduced operating temperatures for aluminum or copper terminations.
- COPPER - ILSCO DE-OX-C series contains flecks of copper providing improved pull-out strength and reduced operating temperatures for copper terminations.



NON-GRIT Catalog Number	Container Size & Type	Packaging
DE-OX -5CC	5cc Packet	Display Carton of 150
DE-OX-5CC-B4	5cc Packet	4 Per Bag, 25 Bags Per Carton
DE-OX-10Z	1 oz. Tube	Display Carton of 50
DE-OX-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-1GAL	1 Gallon Can	1 Can
DE-OX-5GAL	5 Gallon Bucket	1 Bucket
UDE-OX-V-4OZ*+	4 oz. Bottle	Display Carton of 12
UDE-OX-V-8OZ*+	8 oz. Bottle	Display Carton of 12
ZINC Catalog Number	Container Size & Type	Packaging
DE-OX-Z-5CC	5cc Packet	Display Carton of 150
DE-OX-Z-10Z	1 oz. Tube	Display Carton of 50
DE-OX-Z-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-Z-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-Z-1GAL	1 Gallon Can	1 Can
DE-OX-Z-5GAL	5 Gallon Bucket	1 Bucket
COPPER Catalog Number	Container Size & Type	Packaging
DE-OX-C-5CC	5cc Packet	Display Carton of 150
DE-OX-C-10Z	1 oz. Tube	Display Carton of 50
DE-OX-C-4OZ	4 oz. Bottle	Display Carton of 12
DE-OX-C-8OZ	8 oz. Bottle	Display Carton of 12
DE-OX-C-1GAL	1 Gallon Can	1 Can
DE-OX-C-5GAL	5 Gallon Bucket	1 Bucket

\* V denotes synthetic base, chalk color, doesn't stain blankets, etc.

+ Not UL Listed  
UL File E312012