



SKU: NFIMT-14-250-P25

UPC: 0783669207170

Features & Benefits:

Description:ILSCON Disconnect Terminal, Conductor Range 14-16, Male, Nylon Fully Insulated, Blue Color Code, 0.250 x .032in Tab Size, Pack of 25

Specs

Additional Class Attributes

| | |
|-------------------------|-------------|
| Conductor Entry | Funnel wire |
| Connection | Compression |
| Construction Type | Butted |
| End Connection | Male |
| ILSCOs Die Index Number | C |
| Installation Tooling | ILST-22K |
| Installing Dies | Die Set C |
| Insulation Flared End | Yes |
| Insulation Grip | Yes |
| Mounting Hole Type | NA |
| Number of Conductors | 1 |
| Tongue Type | Disconnect |

Dimensions

| | |
|---------------------------------------|--------|
| Height (IN) | 2.88 |
| Height BX (IN) | 7.75 |
| Length (IN) | 3.5 |
| Maximum Wire Insulation Diameter (IN) | 0.177 |
| Weight (LB) | 0.1343 |
| Weight BX (LB) | 8.0576 |
| Width (IN) | 1.21 |
| Width BX (IN) | 9.5 |

Material and Finish

| | |
|---------------------|--------|
| Conductor Material | Copper |
| Connector Finish | Tin |
| Fully Insulated | Yes |
| Insulation Material | Nylon |
| | Brass |

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 25 |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated | No |
| NEMA Code | S-588-3 |
| UPC Code | 78366920717 |

Bolt and Screw Sizes

| | |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

Testing Standards

| | |
|--------------------------|--|
| Prop65 Compliance | WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov |
| UL Control Number | 19X5 |
| UL / CULUS Specification | UL/cUL 310 Listed |
| UL File Number | E474613 |

Color

| | |
|-------|------|
| Color | Blue |
|-------|------|

Conductor Ranges

| | |
|--|-----------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | NA |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | 14 Sol - 16 Sol |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 14 Str - 16 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |

Voltage

| | |
|----------------|-------|
| Voltage Rating | 300 V |
|----------------|-------|

Environment and Temperature

| | |
|--------------------|-------|
| Halogen Free | Yes |
| Temperature Rating | 105°C |