

SKU: NFLB-18-250-P25

UPC: 0783669207361

Features & Benefits:

Description: ILSCON Disconnect Terminal, Conductor Range 18-22, Flag, Nylon Insulated, Red Color Code, 0.250 x .032in Tab Size, Pack of 25



Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
End Connection	Female
ILSCOs Die Index Number	FA
Installation Tooling	ILST-22K
Installing Dies	Die Set FA
Insulation Flared End	Yes
Insulation Grip	Yes
Tongue Type	Flag Disconnect

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.157
Weight (LB)	0.1453
Weight BX (LB)	8.7176
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation Material	Nylon
	Brass

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366920736

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	18 Sol - 22 Sol
Conductor Range CU Stranded (Primary, run, main, line)	18 Str - 22 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	19X5
UL / CULUS Specification	UL/cUL 310 Listed
UL File Number	E474613

Color

Color	Silver
-------	--------

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	Yes
Temperature Rating	105°C