



**SKU:** NFLBD-10-250-P20

**UPC:** 0783669207408

**Features & Benefits:**

**Description:** ILSCON Disconnect Terminal, Conductor Range 10-12, Flag, Double Crimp, Nylon Insulated, Yellow Color Code, 0.250 x .032in Tab Size, Pack of 20

## Specs

### Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
End Connection	Female
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	NA
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	NA
Number of Conductors	1
Tongue Type	Flag Disconnect

### Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Weight (LB)	0.1695
Weight BX (LB)	10.1696
Width (IN)	1.21
Width BX (IN)	9.5

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation Material	Nylon
	Brass

### General

Bag Quantity	20
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366920740

### **Bolt and Screw Sizes**

Mounting Bolt/Stud Size	NA
-------------------------	----

### **Testing Standards**

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	19X5
UL / CULUS Specification	UL/cUL 310 Listed
UL File Number	E474613

### **Color**

Color	Yellow
-------	--------

### **Conductor Ranges**

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

### **Voltage**

Voltage Rating	600 V
----------------	-------

### **Environment and Temperature**

Halogen Free	Yes
Temperature Rating	105°C