



**SKU:** NFLBD-14-250-P25

**UPC:** 0783669207590

**Features & Benefits:**

**Description:** ILSCON Disconnect Terminal, Conductor Range 14-16, Flag, Double Crimp, Nylon Insulated, Blue Color Code, 0.250 x .032in Tab Size, Pack of 25

## Specs

### Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
End Connection	Female
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set B
Insulation Flared End	Yes
Insulation Grip	Yes
Tongue Type	Flag Disconnect

### Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.177
Weight (LB)	0.1761
Weight BX (LB)	10.5656
Width (IN)	1.21
Width BX (IN)	9.5

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation Material	Nylon
	Brass

### General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366920759

### Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

### Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	14 Sol - 16 Sol
Conductor Range CU Stranded (Primary, run, main, line)	14 Str - 16 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

### Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	19X5
UL / CULUS Specification	UL/cUL 310 Listed
UL File Number	E474613

### Color

Color	Blue
-------	------

### Voltage

Voltage Rating	600 V
----------------	-------

### Environment and Temperature

Halogen Free	Yes
Temperature Rating	105°C