



SKU: PDE-11-3/0-CU

UPC: 0783669717785

Features & Benefits:

Description:Power Distribution Block, High SCCR, Line Conductor Range 3/0-14, Load Range 3/0-14, 1 Port Per Pole Line Side, 1 Port Per Pole Load Side, 1 Pole, UL, CSA, Din Rail Mountable

Specs

Additional Class Attributes

Block Size	NA
Mounting Hole Type	Thru
Number of Conductors	2
Number of Poles	1
Number of Ports Per Pole Primary	1
Number of Ports Per Pole Secondary	1

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	3/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	3/0 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	3/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	3/0 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol
High SCCR Conductor Range Line	3/0 Str - 8 Str
High SCCR Conductor Range Load	3/0 Str - 8 Str

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	200 Amps
Fuse Required Class CC Amp Rating	30 Amps
Fuse Required Class GA Amp Rating	60 Amps
Fuse Required Class J Amp Rating	225 Amps
Fuse Required Class RK1 Amp Rating	200 Amps
Fuse Required Class RK5 Amp Rating	60 Amps
Fuse Required Class T Amp Rating	225 Amps

Dimensions

Drive Size Main	6 mm
Drive Size Tap	6 mm
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	0

Height BX (IN)	3.1875
Length (IN)	0
Mounting Bolt/Stud Size (mm)	254
Weight (LB)	0.556
Width (IN)	0
Width BX (IN)	4.0625

Material and Finish

Conductor Material	Copper
Insulation Material	NA
Material	Copper

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
NEMA Code	S-588-4
UPC Code	78366971778

Testing Standards

CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	45U4
UL / CULUS Specification	UL 1953 Listed
UL File Number	E112158

Surge Specifications

Short Circuit Current Rating (SCCR)	100 kA
-------------------------------------	--------

Color

Color	Gray
-------	------

Voltage

Voltage Rating	600 V
----------------	-------