



**SKU:** VRBR-14-12-P25

**UPC:** 0783669215571

**Features & Benefits:**

**Description:**ILSCON Ring Terminal, Conductor Range 14-16, 1/2in Bolt Size, Vinyl Insulated, Blue Color Code, Pack of 25

## Specs

### Additional Class Attributes

|                          |             |
|--------------------------|-------------|
| Conductor Entry          | Funnel wire |
| Connection               | Compression |
| Construction Type        | Brazed      |
| ILSCOs Die Index Number  | A           |
| Installation Tooling     | ILST-22K    |
| Installing Dies          | Die Set A   |
| Insulation Flared End    | Yes         |
| Insulation Grip          | Yes         |
| Mounting Hole Type       | Thru        |
| Number of Conductors     | 1           |
| Number of Mounting Holes | 1           |
| Tongue Type              | Ring        |

### Dimensions

|                                       |         |
|---------------------------------------|---------|
| Length (IN)                           | 1.394   |
| Length (mm)                           | 35.4076 |
| Maximum Wire Insulation Diameter (IN) | 0.177   |
| Mounting Bolt/Stud Size (mm)          | 304.8   |
| Width (IN)                            | 0.756   |
| Width (mm)                            | 19.2024 |

### Material and Finish

|                     |        |
|---------------------|--------|
| Conductor Material  | Copper |
| Connector Finish    | Tin    |
| Fully Insulated     | No     |
| Insulation Material | Vinyl  |
|                     | Copper |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 25              |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366921557     |

### ***Bolt and Screw Sizes***

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 1/2 |
|-------------------------|-----|

### ***Testing Standards***

|                          |   |
|--------------------------|---|
| Prop65 Compliance        | WARNING: Cancer and Reproductive Harm -<br><a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number        | 20U0  |
| UL / CULUS Specification | UL/cUL 486A/B Listed  |
| UL File Number           | E6207   |

### ***Color***

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### ***Conductor Ranges***

|  |                 |
|--|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 14 Sol - 16 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 14 Str - 16 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |

### ***Voltage***

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|

### ***Environment and Temperature***

|                    |       |
|--------------------|-------|
| Halogen Free       | No    |
| Temperature Rating | 105°C |