



**SKU:** VSFBR-10-10-P25

**UPC:** 0783669216653

**Features & Benefits:**

**Description:**ILSCON Spade Terminal, Conductor Range 10-12, Flanged, #10 Bolt Size, Vinyl Insulated, Yellow Color Code, Pack of 25

## Specs

### Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Tongue Type	Spade

### Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Mounting Bolt/Stud Size (mm)	254
Weight (LB)	0.1651
Weight BX (LB)	9.9056
Width (IN)	1.21
Width BX (IN)	9.5

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	Vinyl
Material	Copper

### General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3

UPC Code

78366921665

### ***Bolt and Screw Sizes***

Mounting Bolt/Stud Size

#10

### ***Testing Standards***

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

UL Control Number

20U0

UL / CULUS Specification

UL/cUL 486A/B Listed

UL File Number

E6207

### ***Color***

Color

Yellow

Color Code

Yellow

### ***Conductor Ranges***

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

10 Sol - 12 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

10 Str - 12 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

### ***Voltage***

Voltage Rating

600 V

### ***Environment and Temperature***

Halogen Free

No

Temperature Rating

105°C