



SKU: VSFBR-14-8-P50

UPC: 0783669216592

Features & Benefits:

Description:ILSCON Spade Terminal, Conductor Range 14-16, Flanged, #8 Bolt Size, Vinyl Insulated, Blue Color Code, Pack of 50

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Tongue Type	Spade

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.177
Mounting Bolt/Stud Size (mm)	203.2
Weight (LB)	0.2116
Weight BX (LB)	12.6949
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation Material	Vinyl
	Copper

General

Bag Quantity	50
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3

UPC Code

78366921659

Bolt and Screw Sizes

Mounting Bolt/Stud Size

#8

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

20U0

UL / CULUS Specification

UL/cUL 486A/B Listed

UL File Number

E6207

Color

Color

Blue

Color Code

Blue

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

14 Sol - 16 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

14 Str - 16 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V

Environment and Temperature

Halogen Free

No

Temperature Rating

105°C