



SKU: VSLBR-18-6-P50

UPC: 0783669216974

Features & Benefits:

Description: ILSCON Spade Terminal, Conductor Range 18-22, Locking, #6 Bolt Size, Vinyl Insulated, Red Color Code, Pack of 50

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Spade

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.157
Mounting Bolt/Stud Size (mm)	152.4
Weight (LB)	0.1739
Weight BX (LB)	10.4328
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation Material	Vinyl
	Copper

General

Bag Quantity	50
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No

NEMA Code	S-588-3
UPC Code	78366921697

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#6
-------------------------	----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	20U0
UL / CULUS Specification	UL/cUL 486A/B Listed
UL File Number	E6207

Color

Color	Red
Color Code	Red

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	18 Sol - 22 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	18 Str - 22 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	No
Temperature Rating	75°C