

Technical data sheet

PUR feedback cables · continuous flexing · shielded

LUTZE SUPERFLEX® PLUS (C) PUR FEEDBACK Feedback cables for Allen-Bradley and other systems For highest requirements in drive technology



Identification

Type SU+ (C) PUR FB (5×2×AWG22) 1kV
Part No. [111488.2000](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Incremental encoder cable, termination cable for tacho sensor, brake sensor, speed sensor
 - Through full PUR jacket and TPE conductor insulation optimally suited for c-tracks, extremely harsh operating conditions and aggressive coolants and lubricants
 - Especially for industrial environments in mechanical and system engineering
 - Feedback cables for Allen-Bradley drives
 - Compatible with all major drag chain brands
 - Compliant with NFPA 79, Article 12.9
- Properties
- High protection against electromagnetic interferences (EMI)
 - Braided shield optimised for continuous flexing use
 - Very good alternating bending strength
 - Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
 - Hydrolysis-resistant, microbe-resistant, and rot-resistant
 - UV resistant
 - Industrial and salt water resistant
 - Excellent coolant and lubricant resistance
 - Largely resistant to oils, greases, alcohol-free benzines and kerosene
 - Talc free and silicone free

Construction

Description SUPERFLEX® PLUS (C) PUR FEEDBACK
Number of conductors/cross-section (5×2×AWG22)
Number of conductors 10
Cross-section, metric 0.34 mm²
Cross-section AWG AWG 22
Jacket material PUR

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222
www.lutze.com • info@lutze.com

29.11.2024 • Subject to technical modification
Part No. [111488.2000](#) • Datasheet version: 00

Technical data sheet

PUR feedback cables · continuous flexing · shielded

Jacket color	green similar to RAL 6018
Outer Ø	9.2 mm
Outer Ø	0.362 inch
Surface	adhesion-free
Weight	10.52 kg/100 m
Weight	70.5 Lbs/Mft
Cu Index	5.9 kg/100 m
Cu Index	39 Lbs/Mft

Construction Element 1

Element construction	(5×2×AWG22)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	white/black · black · white/red · red · white/green · green · white/grey · grey · white/orange · orange
Conductor insulation	Special TPE
Cabling	Layer pitch optimised Conductors twisted without mechanical stress

Overall construction

Overall stranding	Stranded pairs Layer pitch optimised Conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Overall shield	Braid shield Tinned copper wires Optical cover approx. 85 %
Jacket characteristics	Flame-retardant Oil resistant Grease-resistant Petrol-resistant (alcohol-free) Kerosene-resistant Silicone free Halogen free

Technical data

Rated voltage	1000 V
Test voltage type	AC 3000 V
Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	7.5×cable OD
Minimum bending radius fixed	5×cable OD
Bending cycles	≥10 Mio
Speed	≤5 m/s
Acceleration	≤50 m/s ²
Torsion	± 30°/m

Technical data sheet

PUR feedback cables · continuous flexing · shielded

Technical Data Element 1

Element construction	(5×2×AWG22)
Insulation resistance at 20 °C	≥200 MΩ×km
Conductor resistance	55 Ω/km
Operating capacitance wire-wire	60 pF/m
Operating capacitance wire-shield	110 pF/m

Approvals/Standards

Approvals	cURus
UL style	AWM 21223
Conformity	CE RoHS REACH
Burning behavior according to	VDE 0482 322-1-2 DIN EN 60332-1-2 IEC 60332-1 UL 1581 part 1080 VW-1 CSA FT 1
Oil resistant according to	UL 1581 4 days at 100 °C DIN EN 60811-404
Halogen free according to	DIN EN 60754-1 IEC 60754-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--