

## Technical data sheet

PUR servo cables · C-track compatible · shielded

### LUTZE SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV

Supply line for Bosch Rexroth and other systems

For highest requirements



#### Identification

Type	SU+ M (C) PUR SE (4G10+(2×1,0)+(2×1,5))
Part No.	<a href="#">111762.1000</a>
BOSCH REXROTH designation*	REL0110

#### Product version

Datasheet version	01
-------------------	----

#### Use/Application/Properties

Application	<ul style="list-style-type: none"><li>• For IndraDyn S MS2N* system and similar</li><li>• Termination cable motor or motor/brake especially for frequency converters and SERVO drives in machine and plant construction, transport and conveyor technology</li><li>• Through full PUR jacket and TPE / HGI conductor insulation optimally suited for c-tracks, extremely harsh operating conditions and aggressive coolants and lubricants</li><li>• Especially for industrial environments in mechanical and system engineering</li></ul>
Properties	<ul style="list-style-type: none"><li>• High protection against electromagnetic interferences (EMI)</li><li>• Braided shield optimised for continuous flexing use</li><li>• Very good alternating bending strength</li><li>• Low adhesion, abrasion-resistant, nick-resistant, tear-resistant</li><li>• Hydrolysis-resistant, microbe-resistant, and rot-resistant</li><li>• Weathering, ozone and UV resistant (normal lighting conditions)</li><li>• Industrial and salt water resistant</li><li>• Excellent coolant and lubricant resistance</li><li>• Largely resistant to oils, greases, alcohol-free benzines and kerosene</li><li>• Silicone free</li></ul>

#### Construction

Description	SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV
Number of conductors/cross-section	(4G10+(2×1.0)+(2×1.5))
Number of conductors	8
Cross-section, metric	10 mm <sup>2</sup>

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222  
www.lutze.com • info@lutze.com

29.11.2024 • Subject to technical modification  
Part No. [111762.1000](#) • Datasheet version: 01

## Technical data sheet

### PUR servo cables · C-track compatible · shielded

---

Jacket material	PUR
Jacket color	orange similar to RAL 2003
Outer Ø	21.9 mm
Outer Ø	0.874 inch
Surface	adhesion-free
Weight	83.7 kg/100 m
Weight	562.43 Lbs/Mft
Cu Index	57 kg/100 m
Cable construction	Construction with two control pairs (digit print 5, 6 and 7, 8)

---

#### Construction Element 1

---

Element construction	4G10
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	black · with white number print · yellow/green
Conductor insulation	TPE

---

#### Construction Element 2

---

Element construction	(2×1,0)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	black · with white number print
Conductor insulation	TPE
Cabling	Conductors twisted in pairs Layer pitch optimised Conductors twisted without mechanical stress
Wrapping	Foil taping
Element shielding	Braid shield tinned copper wires optical cover approx. 85%

---

#### Construction Element 3

---

Element construction	(2×1.5)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	black · with white number print
Conductor insulation	TPE
Cabling	Conductors twisted in pairs Layer pitch optimised Conductors twisted without mechanical stress
Wrapping	Foil taping

---

## Technical data sheet

### PUR servo cables · C-track compatible · shielded

---

Element shielding	Braid shield tinned copper wires optical cover approx. 85%
-------------------	--

---

#### Overall construction

---

Overall stranding	Elements stranded together Layer pitch optimised Conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Overall shield	Braid shield Tinned copper wires Optical cover approx. 85 %
Jacket characteristics	Flame-retardant Oil resistant Grease-resistant Petrol-resistant (alcohol-free) Kerosene-resistant Silicone free Halogen free

---

#### Technical data

---

Rated voltage $U_0/U$	600/1000 V
Rated voltage UL	1000 V
Test voltage type	AC 4000 V
Temperature range moving	-25 °C ... +90 °C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius moving	$7.5 \times D \leq 16 \text{ mm}^2$
Minimum bending radius fixed	$5 \times \text{cable OD}$
Bending cycles	$\geq 10 \text{ Mio}$
Speed	$\leq 5 \text{ m/s}$
Acceleration	$\leq 50 \text{ m/s}^2$
Torsion	$\pm 30^\circ/\text{m}$

---

#### Technical Data Element 1

---

Element construction	4G10
Insulation resistance at 20 °C	$\geq 1000 \text{ M}\Omega \times \text{km}$
Operating capacitance wire-wire	approx. 81 pF/m
Operating capacitance wire-shield	approx. 146 pF/m

---

#### Technical Data Element 2

---

Element construction	(2×1,0)
Insulation resistance at 20 °C	$1000 \text{ M}\Omega \times \text{km}$
Operating capacitance wire-wire	approx. 135 pF/m
Operating capacitance wire-shield	approx. 243 pF/m

---

## Technical data sheet

PUR servo cables · C-track compatible · shielded

---

### Technical Data Element 3

---

Element construction	(2×1.5)
Insulation resistance at 20 °C	1000 MΩ×km
Operating capacitance wire-wire	approx.157 pF/m
Operating capacitance wire-shield	approx.283 pF/m

---

### Approvals/Standards

---

Approvals	cURus
UL style	AWM 21209
Conformity	CE RoHS REACH TSCA
Burning behavior according to	VDE 0482-332-1-2 DIN EN 60332-1-2 IEC 60332-1-2 UL VW1, FT1 UL 1581 UL 2556
Oil resistant according to	UL 4d100C DIN EN 60811-404 DIN EN 50363-10-2
Halogen free according to	IEC 60754-1 DIN EN 60754-1 DIN 0472 Part 815

---

### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU * Cables for MS2N motors. Bosch Rexroth and REL article designations are registered trademarks of the Bosch Group.
------	--