

Technical data sheet

PUR actuator-sensor cables · c-track suitable

LÜTZE SUPERFLEX® TRONIC AS PUR, unshielded
For highest requirements



Identification

Type SU TR AS PUR 4×0,34
Part No. [117244.2000](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Connecting cable for the actuator-sensor technology
 - For continuous flexing use e.g. in c-tracks or free movement in the automation technology, transport and conveyor technology, machine tool manufacture
 - PUR jacket optimally suited for harsh operating conditions and aggressive coolants and lubricants
- Properties
- Very good alternating bending strength
 - Good pressure and roll-over resistance
 - Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
 - Hydrolysis-resistant, microbe-resistant, and rot-resistant
 - Weathering, ozone and UV resistant (normal lighting conditions)
 - Industrial and salt water resistant
 - Excellent coolant and lubricant resistance
 - Largely resistant to oils, greases, alcohol-free benzines and kerosene
 - Silicone free
 - Halogen free

Construction

Description SUPERFLEX® TRONIC AS PUR
Number of conductors/cross-section 4×0.34
Number of conductors 4
Cross-section, metric 0.34 mm²
Cross-section AWG AWG 22
Jacket material PUR
Jacket color black similar to RAL 9005
Outer Ø 4.5 mm
Outer Ø 0.177 inch
Surface adhesion-free

USA: LÜTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222
www.lutze.com • info@lutze.com

26.11.2024 • Subject to technical modification
Part No. [117244.2000](#) • Datasheet version: 00

Technical data sheet

PUR actuator-sensor cables · c-track suitable

Weight	3 kg/100 m
Weight	20.1 Lbs/Mft
Cu Index	1.32 kg/100 m
Cu Index	8.8 Lbs/Mft

Construction Element 1

Element construction	4×0.34
Conductor construction	42×0.10
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	brown · white · blue · black
Conductor marking standard	EN 60947-5-2
Conductor insulation	TPE

Overall construction

Overall stranding	Conductors layered construction Layer pitch optimised Conductors twisted without mechanical stress
Jacket characteristics	Flame-retardant Oil resistant Grease-resistant Petrol-resistant (alcohol-free) Kerosene-resistant Silicone free Halogen free

Technical data

Rated voltage	300 V
Test voltage type	AC 1500 V
Temperature according to UL	80 °C
Temperature range moving	-20 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	7.5×cable OD
Minimum bending radius fixed	4×cable OD
Bending cycles	≥5 Mio
Speed	≤4
Acceleration	≤5

Technical Data Element 1

Element construction	4×0.34
Insulation resistance at 20 °C	≥100 MΩ×km
Conductor resistance	≤65.3 Ω/km
Operating capacitance wire-wire	≤60 pF/m

Technical data sheet

PUR actuator-sensor cables · c-track suitable

Approvals/Standards

Approvals	cURus
UL style	AWM 20549
Conformity	CE RoHS REACH TSCA
Burning behavior according to	IEC 60332-2 UL 1581 Horizontal Flame Test CSA FT 1
Oil resistant according to	UL 758 UL 4d100C DIN EN 60811-404
Halogen free according to	EN 60754-1 VDE 0482-754-1
UV-resistant according to	UL 1581/2556-300h

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--