#### USB 3.0 panel connector with M22 thread for front installation USB connector Type A on straight USB plug Type A with PVC cable





Identification

Type USB-3.0 A/A F/M 0.3m PVC

Part No. 490113.0030

**Product version** 

00 Datasheet version

General

USB-A Design

Form male 1 USB 3.0 female Type A Form male 2 USB 3.0 male Type A

3 Degree of pollution

Contact resistance  $<30 \text{ m}\Omega$ 

Degree of protection IP65 UL50E Type 2, 3R, 4, 4X, 12, 13 in closed and IP20 in inserted position

Housing material PA, PVC Cover **TPU** 

Contact material CuSn, gold-plated Mounting Front installation

Installation depth approx.70 mm

Number of conductors/cross-section (2×AWG24 + 1×2×AWG28 + 2×(1×2×AWG28)St)StC

**PVC** Jacket material Jacket color black Cable diameter 6.1 mm 6×cable OD Bending radius Operation temperature range -5 °C ... +70 °C -25 °C ... +80 °C Temperature range fixed -5 °C ... +70 °C Temperature range moving 29.5 × 45 mm Dimensions (Ø×d)


Mechanical service life 1500 insertion cycles

Weight/unit 0.046 kg

PU (units) 1

**USA: LUTZE INC.** 

13330 South Ridge Drive • Charlotte, NC 28273, USA Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223 www.lutze.com • info@lutze.com






## **Technical data sheet**

# Actuator sensor interface · USB Panel pass through devices


Technical data	
Rated voltage U <sub>N</sub>	AC/DC 5 V
Operating voltage max.	30 V
Rated current	0.9 A
Pole number	9
Cable length	0.3 m
Transfer rate	5 Gbit/s
USB standard	3.0
Contact type	1:1
Shielding	shielded
Approvals/Standards	
Approvals	cULus Listed (E326112)
Equipment/Spare parts	
Accessories	Included in the delivery: attached safety cap

#### **Dimensions**







## PIN assignment



#### Front view



## Mounting diagram



## Pin layout

