

## Technical data sheet

### Flexible VFD Cable XHHW-2 with UL Approval

#### LUTZE DRIVEFLEX® XLPE (C) PVC, Shielded for Stationary Applications



#### Identification

Type DR XLPE (C) PVC (4GAWG12)  
Part No. [A1061204](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

- Application
- Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives
  - Cable design for harsh industrial environments and operating conditions with high noise levels
  - Type XHHW-2 insulation offering smaller ODs for general VFD applications
  - Thermoset XLPE offering superior overload and short-circuit temperature
  - Compliant with NFPA 79 requirements
  - TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments
  - WTTC – wind turbine tray cable rating for use in wind power generation
  - Dry, damp or wet conditions
- Properties
- Flexible XLPE conductors
  - Reduced cable diameter
  - High insulation resistance
  - Low capacitance insulation
  - Effective dual layer shield for EMC compliance
  - Specially formulated jacket for oil resistance and easy strip design
  - Non-wicking fillers
  - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
  - Crush impact resistant
  - Gas/vapor-tight sheath per UL 1277
  - Sunlight resistant
  - Flame-retardant
  - Direct burial
  - Talc free and silicone free

#### Construction

Description DRIVEFLEX® XLPE (C) PVC  
Number of conductors/cross-section (4×AWG12)

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

17.04.2023 • Subject to technical modification  
Part No. [A1061204](#) • Datasheet version: 00

## Technical data sheet

### Flexible VFD Cable XHHW-2 with UL Approval

---

Number of conductors	4
Cross-section AWG	AWG 12
Jacket material	PVC
Jacket color	black similar to RAL 9005
Outer Ø	13 mm
Outer Ø	0.51 inch
Weight	208 Lbs/Mft
Cu Index	118 Lbs/Mft

---

#### Construction Element 1

---

Element construction	65/30
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	XLPE XHHW-2 Wet/Dry

---

#### Overall construction

---

Drain wire	CU-wire tin-plated
Overall shield	Foil shield Braid shield tinned copper wires optical cover approx. 80 %
Jacket characteristics	Oil resistant Silicone-free

---

#### Technical data

---

Rated voltage $U_N$	600 V 90C UL TC-ER-JP 1000 V Flexible VFD servo cable Cable, 1000 V 105C AWM 1000 V WTTC
Temperature range fixed	-40 °C ... +105 °C
Bending radius	6×cable OD

---

#### Technical Data Element 1

---

Element construction	65/30
----------------------	-------

## Technical data sheet

### Flexible VFD Cable XHHW-2 with UL Approval

---

#### Approvals/Standards

---

Approvals	UL Flexible Motor Supply Cable Flexible VFD Servo Cable cULus TC-ER-JP UL DP-1 Meets NEC 336,392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 Submersible Pump cUL TC CIC FT4 UL 1277 cURus
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

#### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--