

## Technical data sheet

### Cable fittings and accessories

---

#### LUTZE TOP-T Fittings Metric Plastic metric



---

#### Identification

---

Type TOP-T Plastic M32×1,5  
Part No. [FPM32G](#)

---

#### Product version

---

Datasheet version 00

---

#### Use/Application/Properties

---

Properties

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- manufactured acc. to EN 62444

---

#### Technical data

---

Clamping range D 18 mm – 25 mm  
Clamping range D 0.709 inch – 0.984 inch  
Temperature range -20 °C ... +100 °C  
-4 °F ... +212 °F  
Intermittent temperature range -40 °C ... +150 °C  
-40 °F ... +302 °F  
Degree of protection IP68  
Diameter D 42 mm  
Thread form metric  
Thread standard metric acc. to EN 60423  
Thread G M32×1.5  
TL 15 mm  
TD 32 mm  
H 41 mm

---

#### Construction

---

Material PA 6  
Material seal CR chloroprene rubber

---

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

18.04.2023 • Subject to technical modification  
Part No. [FPM32G](#) • Datasheet version: 00

## Technical data sheet

### Cable fittings and accessories

---

Color silver grey similar to RAL 7001

---

#### General

---

PU (units) 20

---

#### Approvals/Standards

---

Approvals cULus

---

#### Notes and Comments

---

Note Locknuts sold separately

---

#### Dimensions

