

## Technical data sheet

### Cable fittings and accessories

---

#### LUTZE TOP-T Fittings NPT Plastic NPT



---

#### Identification

Type TOP-T Plastic NPT 1/2"  
Part No. [FPNPT12B](#)

---

#### Product version

Datasheet version 00

---

#### Use/Application/Properties

Properties

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- manufactured acc. to EN 62444

---

#### Technical data

Clamping range D 10 mm – 14 mm  
Clamping range D 0.394 inch – 0.551 inch  
Temperature range -20 °C ... +100 °C  
-4 °F ... +212 °F  
Intermittent temperature range -40 °C ... +150 °C  
-40 °F ... +302 °F  
Degree of protection IP68  
Thread form NPT  
Thread G NPT 1/2"  
SW 30.9 mm  
TL 11 mm  
TD 21.3 mm  
H 31 mm

---

#### Construction

Material PA 6  
Material seal CR chloroprene rubber  
Color schwarz ähnlich RAL 9005

---

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

18.04.2023 • Subject to technical modification  
Part No. [FPNPT12B](#) • Datasheet version: 00

## Technical data sheet

### Cable fittings and accessories

---

#### General

---

PU (units) 20

---

#### Approvals/Standards

---

Approvals cULus

---

#### Notes and Comments

---

Note Locknuts sold separately

---

#### Dimensions

