

Technical data sheet

Cable fittings and accessories

LUTZE TOP-T Fittings NPT Plastic NPT



Identification

Type TOP-T Plastic NPT 3/8"
Part No. [FPNPT38B](#)

Product version

Datasheet version 00

Use/Application/Properties

Properties

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- manufactured acc. to EN 62444

Technical data

Clamping range D 5 mm – 10 mm
Clamping range D 0.197 inch – 0.394 inch
Temperature range -20 °C ... +100 °C
-4 °F ... +212 °F
Intermittent temperature range -40 °C ... +150 °C
-40 °F ... +302 °F
Degree of protection IP68
Thread form NPT
Thread G NPT 3/8"
SW 22 mm
TL 15 mm
TD 17.1 mm
H 29 mm

Construction

Material PA 6
Material seal CR chloroprene rubber
Color schwarz ähnlich RAL 9005

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

18.04.2023 • Subject to technical modification
Part No. [FPNPT38B](#) • Datasheet version: 00

Technical data sheet

Cable fittings and accessories

General

PU (units) 20

Approvals/Standards

Approvals cURus

Notes and Comments

Note Locknuts sold separately

Dimensions

