

DSN30 Switch-Rated Plugs & Receptacles – 30 A

UL/CSA Ratings

- **Max Amperage & Voltage**
30 A, 600 VAC
- **Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit Disconnect Switching
- **Horsepower Ratings**

120V	1Ø	2 hp
240V	1Ø	3 hp
208V	3Ø	5 hp
240V	3Ø	5 hp
480V	3Ø	15 hp
600V	3Ø	15 hp
- **Short Circuit Rating**
100kA Close & Withstand
Testing was performed with RK1 current limiting fuses sized at 400% of the highest full load motor ampacity associated with the devices hp rating.
- **Environmental Ratings**
Type 4X/IP69/IP69K*
*Also meets IP66/IP67 requirements
- **Temperature Range**
Min -40°F/Max 140°F
See pg 258 for temps below -15°F.
- **Wiring Capacity**
Min 14 AWG Max 8 AWG Aux
Contacts - 14 AWG
- **Certifications**
UL 2682, UL 1682, CSA 182.1

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

Voltage	Polarity	Part # Poly	Part # Poly
120V	1P+N+G	63-34165	63-38165
120 208V	3P+N+G	63-34167	63-38167
125V	1P+N+G	63-34075	63-38075
125 250V	2P+N+G	63-34076	63-38076
208V	2P+G	63-34162	63-38162
208V	3P+G	63-34163	63-38163
250V	2P+G	63-34072	63-38072
250V	3P+G	63-34073	63-38073
277V	1P+N+G	63-34045	63-38045
277 480V	3P+N+G	63-34047	63-38047
347 600V	3P+N+G	63-34147	63-38147
480V	2P+G	63-34042	63-38042
480V	3P+G	63-34043	63-38043
600V	2P+G	63-34142	63-38142
600V	3P+G	63-34143	63-38143

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800-433-7642.

Main Options



Auxiliary/Pilot Contacts



Mushroom Pawl



Padlock Pawl



Closed Lid Configuration

Recommended for cord applications to keep lid tucked in to avoid damage.

Receptacle Options

Suffix

Inlet Options

Suffix

With 2 Auxiliary/Pilot Contacts	Recept # - 972	With 2 Auxiliary/Pilot Contacts	Inlet # - 972
Straight Insertion	Recept # - 352	Self-Ejecting Plug Release	Inlet # - 338
Self-Ejecting Connector Release	Recept # - 354	With No Lockout Hole	Inlet # - A155
Mushroom Pawl	Recept # - 375	For Auxiliary Switch	Inlet # - NNF*
Padlock Pawl	Recept # - 843	Notes: * Order inlet with P+N+G configuration and receptacle with P+G configuration.	
Padlockable Mushroom Pawl	Recept # - 375-843		
Metal Pawl	Recept # - 824		
Closed Lid Configuration	Recept # - NC		
With Auxiliary Switch	Recept # - 270+		



Notes: + Not UL/CSA listed.

! See pages 235-244 for detailed information on these options


Order Example: 480V DSN30 + 2 auxiliary contacts
DSN30 Inlet 3P+G = 63-38043-972

INSTALLATION ACCESSORIES – SIZE 2


HANDLES


HANDLE w/NPT		Part # Poly	Part # Metal
	1/2"	512P0N05	592P0N05
	3/4"	512P0N07	592P0N07
	1"	512P0N10	592P0N10
	1 1/4"	512P0N12	-

For available cord grips, see page 167.


POLY HANDLE w/CORD GRIP		Cable Range	Part #
		.350 - .520"	712P0BP6
		.520 - .680"	712P0CP5
		.680 - .980"	712P0DP4
		.980 - 1.260"	712P0EP4


METAL HANDLE w/CORD GRIP		Cable Range	Part #
		.438 - .500"	792P0BS3
		.500 - .562"	792P0BS4
		.562 - .625"	792P0CS2
		.625 - .750"	792P0CS4
		.750 - .875"	792P0DS1
		.875 - 1.000"	792P0DS3


POLY HANDLE		Cable Range	Part #
		.20 - .83"	512P0D21

POLY HANDLE w/CLAMP & BUSHING		Cable Range	Part #
		.750 - .875"	712P0S14
		.875 - 1.000"	712P0S16
		1.000 - 1.125"	712P0S18
		1.125 - 1.250"	712P0S20
		1.250 - 1.375"	712P0S22


ANGLES

POLY ANGLE		Angle	Part #
	30°	512M3	


POLY ANGLE		Angle	Part #	Notes
	70°	512M7	Panel mounting only.	



METAL ANGLE		Angle	Part #
	0°	592M0	

METAL ANGLE		Angle	Part #
	30°	592M3	

METAL ANGLE		Angle	Part #	Notes
	FS/FD Box 30°	792M3FS	* Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.	


BOXES

POLY CONDUIT ENTRY w/NPT		Angle	Size	Part #	Notes
	30°	1/2"	512B3N05	* Interior volume with receptacle installed.	
	30°	3/4"	512B3N07		

POLY WALL BOX w/ANGLE		Angle	Part #	Notes
	70°	512C7000	70° poly boxes are not drilled. Contact Customer Service if factory drilled is required.	
	Ground Bar	51AA089	* Interior volume with receptacle installed.	


POLY ANGLE w/METAL WALL BOX w/NPT		Angle	Size	Part #	Notes
	70°	1/2"	712C7N05	* Interior volume with receptacle installed.	
	70°	3/4"	712C7N07		
	70°	1"	712C7N10		
	70°	1 1/4"	712C7N12		
	70°	1 1/2"	712C7N15		

METAL BOX w/NPT		Angle	Size	Part #
	0°	1/2"	7T1F0N05	
	0°	3/4"	7T1F0N07	
	0°	1"	7T1F0N10	
	0°	1 1/4"	7T1F0N12	

POLY ANGLE w/METAL BOX w/NPT		Angle	Size	Part #	Notes
	30°	1/2"	712C3N05	* Interior volume with receptacle installed.	
	30°	3/4"	712C3N07		
	30°	1"	712C3N10		
	30°	1 1/4"	712C3N12		

NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.


MISCELLANEOUS ACCESSORIES


FINGER DRAWPLATES		Part #	Notes
	61-3A346	Set of Two (2) Recommended for cord to cord assembly applications, for easier connector closure.	

PROTECTIVE INLET/PLUG CAP		Part #	Notes
	61-3A426	For Inlets/Plugs Only.	

PADLOCKABLE INLET/PLUG CAP		Part #	Notes
	61-3A826	For Inlets/Plugs Only.	

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP		Part #	Notes
	61-3A226	Metal - For Inlets/Plugs Only. -A155 suffix required to maintain water ingress protection.	

SCREWDRIVER FOR TERMINAL SCREWS		Part #	Notes
	SD18	Klein 608-3 1/8" cabinet with 3" round shank.	

RECEPTACLE LOCKING PIN		Part #	Notes
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.	