



## MCF-16.3/MM 3U rack for LLM-336R or DLM-336R modem cards

### Introduction

The MuLogic MCF-16.3/MM is an industrial grade, 19" 3U (5.25" H) chassis with slots for up to 16 modem cards. The chassis can be used for LLM-336R and DLM-336R modem cards operating in asynchronous serial data mode.

The MCF-16.3/MM is equipped with 8-pin modular jack connectors for both serial data interface and line connection.




On request, the chassis can be delivered with a screw terminal connector for using the RS485 interfaces of the LLM-336R modem on a RS485 bus. For certain SCADA applications this will provide a dramatic reduction in cabling.

Electrical power is applied via screw terminal connectors. The power range can be 9..36Vdc, 10..28Vac, or 18..72Vdc depending on the type of modem used.

### Features

- High density modem chassis for up to 16 modems.
- 19" 3U (3HE).
- 8-pin modular jacks for serial data.
- 8-pin modular jacks for lines.
- DB37 for 16 x 2-wire line optional.
- 9..72Vdc or 10..28Vac power supply.
- RS485 bus optional.
- Easy, cost saving installation.

## Dimensions and connectors



MuLogic b.v. Olivier van Noortstraat 4 3124 LA Schiedam The Netherlands Tel: +31 10 4700077 Fax: +31 10 4700958  
E-mail: [inform@mulogic.com](mailto:inform@mulogic.com)