



UCF-16.3 Universal Modem chassis



3U card rack for DLM-336R, LLM-336R, LLM-336R.Eth and DSL-4608R modem card sets

The UCF-16.3 is a 3U, 19" chassis for those products that are also available in the rugged desktop housing (like e.g. the LLM-336S). These products consist of a eurocard size (100x160 mm) modem card and a 100x70 mm interface card. The modem and interface cards interconnect inside the chassis. The UCF-16.3 therefore has no back plane: all connections, including the power, are made externally.

The UCF-16.3 card frame allows for flexible housing of a mix of various MuLogic products, without a PSU or with a single or dual PSU.

Examples



UCF-16.3 with 16 modem cards




UCF-16.3 with 15 modem cards and one PSU



UCF-16.3 with 14 modem cards and 2 PSUs

Back panel




Rear view of the UCF-16.3

The modem and interface cards interconnect inside the chassis. The UCF-16.3 therefore has no back plane: all connections, including the power, are made externally.

The screw terminal sockets (2 per panel), allow for a very flexible power supply arrangement, such as "daisy chaining", feeding from different sources, looping etc. .





Examples of supply power wiring



Power Supply

All MuLogic rack cards can be powered directly from 9..36Vdc (10..28Vac) or 18..72Vdc sources. If these voltages are not available, mains power supplies can be mounted inside the rack, in an additional UCF-16.3 rack or standalone (e.g. DIN-rail mounted PSUs or AC transformers)

Mechanical Details



[Back to products page](#)

MuLogic b.v. - Olivier van Noortstraat 4, 3124 LA - Schiedam - The Netherlands - Tel: +31 10 4700077 - Fax: +31 10 4700958
E-mail:inform@mulogic.com