



CONNECTIONS
LINE 1-1
LINE 2-3

ROTATION: CW LEAD END

OPTIONAL
WHEN AUX WINDING IS SPECIFIED AS
1/2 COPPER & 1/2 ALUMINUM.
COPPER WINDING MUST BE IN BORE
PER DIAGRAM.

NIDEC CONFIDENTIAL
NIDEC MOTOR CORPORATION 06-FEB-13

REVISION DESCRIPTION FOR: C7076-00	SCALE: NONE	UNITS: IN	TITLE: DIAGRAM OF CONNECTIONS	NIDEC MOTOR CORPORATION
UPDATED CONNECTION DIAGRAM	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		ISSUED BY: A. SANCHEZ	APPROVED BY: J. SCHRADER
MATERIAL:	INCHES: .XX = ± .01 .XXX = ± .005	MM:	CODE: D04	DRWG NO.: 316118
MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/EC AND REGULATION EC 1907/2006 (REACH) AS AMENDED			REVISION DATE: 06-FEB-13	REV: D
ANGLES: X° = ± 1°			REV: 1	SHEET NUMBER: 1 OF 1
			DWG SIZE: B	SOLDEDGE

WMCB (MAR-2011)